

## Item#: **77519 LED HIGH WATTAGE 360° LAMP**

REPLACEMENT LAMPS FOR OUTDOOR POLE/ARM MOUNTED DECORATIVE LUMINAIRES (TYPE B)


## **FEATURES**

- Environmentally friendly; uses less energy than a traditional lamp.
- 360° optical design that provides even light distribution.
- High Voltage Surge Protection (6KV).
- · Hollow heat sink for increased cooling air flow.
- High lumen output.
- Silicone gaskets.

## **APPLICATION**

Replacement lamps for top post, high bays, parking lots and street lighting.

## **LIGHT DISTRIBUTION CURVE**



### **ELECTRICAL**

ELECTRICAL			
Wattage	27W		
Voltage	120-277V		
Current	0.27A		
Power Factor	0.9		
Total Harmonic Distortion (THD)	12.2		
LIGHTING PERFORMANCE			
Lumens	3510		
Lumens Per Watt (LPW)	130		
Color Temperature (CCT)	5000K		
Color Rendering (CRI)	80		
R9 (Red Value)	N/A		
R13 (Skin Tones)	N/A		
Beam Angle	360°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B1 - U5 - G2		
Dimmable Lighting Control	ONT DIMMAREL		
ENVIRONMENT			
Operating Temperature	-40° ~ 122°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP63		
Fixture Type	Enclosed		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	JuFei 2835		
CONSTRUCTION			
Housing	Aluminum / PC		
Lens	Clear		
Base / Power Supply	E26 - Medium		

## **QUALIFICATIONS**



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.


# Item#: **77519 LED HIGH WATTAGE 360° LAMP**

## **DIMENSIONS** (Inches)

Length (MOL)	7.3"
Width/Diameter (MOD)	3.8"
Net Weight (Lbs)	1.7

## **SUPPORTING DOCUMENTS** (Grey = not available at this time.)

	- ()
Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
Photometric	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	12	10899645001650	18" x 13.5" x 10"	25.4
Individual Box	1	899645001653	4.3" x 4.3" x 9.3"	1.9
Country of Origin	China			
HS Tariff	8539.50.0010			

## **ORDERING**

ITEM#	DESCRIPTION	CASE
77519	LED 27WT30/50K/360°/CL/120-277V/MED	12

## **ADDITIONAL INFORMATION:**

Family Item(s): 19619/3000K

**TOP VIEW** 

