



SELECTABLE
COLOR
TEMPERATURE

Item#: **88248**
LED TONE-SELECT™ PRESTIGE™ II
CEILING LIGHT
INDOOR FIXTURE

FEATURES

- Selectable color temperature
- LED surface mount fixture provides glare free illumination and even light distribution with a clean, modern look.
- Diffusing lens
- Low profile design

APPLICATION

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, hallways, lobbies and other residential and commercial applications.

ELECTRICAL

Wattage	21W
Voltage	120V
Current	180mA
Power Factor	0.9
Total Harmonic Distortion (THD)	--

LIGHTING PERFORMANCE

Lumens	1470
Lumens Per Watt (LPW)	70
Color Temperature (CCT)	27K / 30K / 35K / 40K / 50K
Color Rendering (CRI)	80
R9 (Red Value)	--
R13 (Skin Tones)	--
Beam Angle	220°
Light Distribution	--
Dimmable Lighting Control	<i>Dimmable</i> see compatibility report

ENVIRONMENT

Operating Temperature	-4° ~ 104°F
Suitable Location	DAMP Indoor / Covered Ceilings
Ingress Protection Rating	IP20

LIFESPAN

Average Life (Hours)	35,000
Warranty (Years)	3

COMPONENTS

LED Light Source	--
Driver	--

CONSTRUCTION

Housing	--
Base / Power Supply	Hard Wired
Finish	Brushed Nickel

QUALIFICATIONS

ETL Model Number	TSPC-21-D5CT-SL-N-8
Energy Star® Model Number	84288



Visit www.energystar.gov to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **88248**


LED TONE-SELECT™ PRESTIGE™ II CEILING LIGHT

DIMENSIONS (Inches)

Width/Diameter (MOD)	13"
Height	2.3"
Net Weight (Lbs)	--

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
Dimmer Compatibility	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	6	10811768028079	15.8" x 14.7" x 14.7"	13.7
Individual Box	1	811768028072	13.9" x 13.9" x 2.4"	2.3
Country of Origin	China			
HS Tariff	--			

ORDERING

ITEM#	DESCRIPTION	CASE
88248	LED 13IN TONE-SELECT™ PRESTIGE™ II CEILING LIGHT/21W/27-30-35-40-50K/DIMM/120V/WHT/BKN - ENERGY STAR®	6