

LED TONE-SELECT[™] CFL DIRECT WIRE MEDIUM BASE REPLACEMENT LAMP FOR CFL

- Adjustable color temperature for custom lighting

Replaces traditional CFL lamps frequently used in

*Not suitable for use with emergency exits or lighting.

Universal voltage using direct wire.Rotating base for precise positioning.

Item#: 74519

FEATURES

application. • Exceptional efficacy.

- APPLICATION

downlights and sconces.

ELECTRICAL

SELECTABLE COLOR TEMPERATURE

LEUTINAL		
Wattage	8W	
Voltage	120-277V	
Current	75mA	
Power Factor	0.9	
LIGHTING PERFORMANCE		
Lumens	950-1050	
Lumens Per Watt (LPW)	119-131	
Color Temperature (CCT)	27K / 30K / 35K / 40K / 50K	
Color Rendering (CRI)	83	
Beam Angle	120°	
Light Distribution	Type III, Very Short	
BUG Rating (Backlight, Uplight, and Glare)	B0 - U3 - G1	
Dimmable Lighting Control		
ENVIRONMENT		
Operating Temperature	-4° ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Fixture Type	Enclosed	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Samsung	
CONSTRUCTION		
Housing	Aluminum / PC	
Lens	Frosted	
Base / Power Supply	Medium	
Finish	White / Silver	

QUALIFICATIONS




Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **74519** LED TONE-SELECT[™] CFL DIRECT WIRE

DIMENSIONS (Inches)

Length (MOL)	6.9"
Width/Diameter (MOD)	1.4"
Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)		
Product Sheet VIEW		
IES Download from Web Item	VIEW	
LM79	VIEW	
LM80	VIEW	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	50	10899645001070	17.7" x 8.9" x 7.7"	
Inner Carton	10	20899645001077		
Individual Box	1	899645001073	7.3" x 1.7" x 1.7"	
Country of Origin	China			
HS Tariff	8539.50.0010			

ORDERING

ITEM#	DESCRIPTION	TITLE 20	CASE
74519	LED TONE-SELECT™ 8WT10/27-30-35-40-50K/120°/FR/120-277V/MED	Yes	50

ADDITIONAL INFORMATION:

CCT DIP SWITCH SETTINGS

CCT	Switch 1	Switch 2	Switch 3
2700K		ON	
3000K	ON		ON
3500K		ON	ON
4000K	ON		
5000K			ON

TOP VIEW

