

SELECTABLE
COLOR
TEMPERATURE

Item#: **94519**
LED TONE-SELECT™ CFL DIRECT WIRE
MEDIUM BASE REPLACEMENT LAMP FOR CFL

FEATURES

- Adjustable color temperature for custom lighting application.
- Exceptional efficacy.
- Universal voltage using direct wire.
- Rotating base for precise positioning.

- APPLICATION


Replaces traditional CFL lamps frequently used in downlights and sconces.

**Not suitable for use with emergency exits or lighting.*

ELECTRICAL

Wattage	11W
Voltage	120-277V
Current	100mA
Power Factor	0.9

LIGHTING PERFORMANCE

Lumens	1400-1500
Lumens Per Watt (LPW)	127-136
Color Temperature (CCT)	27K / 30K / 35K / 40K / 50K
Color Rendering (CRI)	83
Beam Angle	120°
Light Distribution	Type III, Very Short
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1
Dimmable Lighting Control	

ENVIRONMENT

Operating Temperature	-4° ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP20
Fixture Type	Enclosed

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Samsung
------------------	---------

CONSTRUCTION

Housing	Aluminum / PC
Lens	Frosted
Base / Power Supply	Medium
Finish	White / Silver

QUALIFICATIONS




Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

Item#: **94519**
LED TONE-SELECT™ CFL DIRECT WIRE

DIMENSIONS (Inches)

Length (MOL)	6.9"
Width/Diameter (MOD)	1.4"
Weight (Lbs)	--



SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	50	10811768022237	17.7" x 8.9" x 7.7"	--
Inner Carton	10	20811768022234	--	--
Individual Box	1	811768022230	7.3" x 1.7" x 1.7"	--
Country of Origin	China			
HS Tariff	8539.50.0010			


ORDERING

ITEM#	DESCRIPTION	TITLE 20	CASE
94519	LED TONE-SELECT™ 11WT10/27-30-35-40-50K/120°/FR/120-277V/MED	Yes	50

ADDITIONAL INFORMATION:

CCT DIP SWITCH SETTINGS

CCT	Switch 1	Switch 2	Switch 3
2700K	--	ON	--
3000K	ON	--	ON
3500K	--	ON	ON
4000K	ON	--	--
5000K	--	--	ON



ITEM INFORMATION