

Item#: 98638 LED MINI WALL PACK

OUTDOOR NON-CUTOFF AND SEMI-CUTOFF WALL-MOUNTED AREA LUMINAIRES

## **FEATURES**

- · Easy installation
- Replaces 50W HID
- Sealed housing for outdoor applications
- · Polycarbonate optical lens

# **APPLICATION**

Ideal for security, pathway and perimeter lighting, building entry ways and walkways.

#### **ELECTRICAL**

Wattage	23W
Voltage	120-277V
Current	0.23A
Power Factor	0.9
Total Harmonic Distortion (THD)	13.2
LIGHTING PERFORMANCE	
Lumens	3174
Lumans Par Watt (LDW)	136

Lumens	3174
Lumens Per Watt (LPW)	136
Color Temperature (CCT)	4000K
Color Rendering (CRI)	73
R9 (Red Value)	-34
R13 (Skin Tones)	
Beam Angle	90°

BUG Rating (Backlight, Uplight, and Glare)

B1 - U3 - G2

Dimmable Lighting Control

"Dimmable 0-10V, Range 10% - 100%

Type IV, Very Short

## **ENVIRONMENT**

**Light Distribution** 

Operating Temperature	-22° ~ 113°F
Suitable Location	WET
Ingress Protection Rating	IP65

## **LIFESPAN**

Average Life (Hours)	50,000
Warranty (Years)	5

## **COMPONENTS**

LED Light Source	Luxeon 3030 2D
Driver	WP-HLA-030U

## **CONSTRUCTION**

Housing	Aluminum Alloy / PC		
Lens	Clear		
Base / Power Supply	Hard Wired		
Finish	Black		

#### **QUALIFICATIONS**






Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

# Item#: 98638 LED MINI WALL PACK

## **DIMENSIONS** (Inches)

Length	8.3"
Width	5.5"
Height	3.2"
Net Weight (Lbs)	

<b>SUPPORTING DOCUMENTS</b> (Grey = not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	
IES Download from Web Item	VIEW	
LM79	VIEW	
LM80	VIEW	



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	8	811768020281	5.6" x 3.9" x 8.5"	16.3
Individual Box	1	10811768020288		2
Country of Origin	China			
HS Tariff	9405.11.8020			

#### **ORDERING**

ITEM#	DESCRIPTION	CASE
98638	LED MINI WALL PACK/25W/40K/CL/DIMM/120-277V/BLK - <b>DLC</b> °	8

## **ADDITIONAL INFORMATION:**

**Note:** To prevent water damage which may shorten the life of an exterior mounted fixture; the fixture should be properly weather sealed according to the installation instructions or between the fixture base and mounting surface. Damage due to improper installation may void the warranty.