

2 HEAD LED EXIT SIGN, RED, DAMP RATED

This safety light fixture includes a battery backup to provide 90-minutes of light during a power failure. The 2 LED heads can be swiveled left/right to position the light beam where you need it. Mount this fixture on ceiling or wall with included mounting hardware.

MODELS

EX_2H-RED-6PK


LIGHT DISTRIBUTION ANGLE

AC SPECTRUM DISTRIBUTION

CIE1931Chromaticity Diagram


0.6915 y = 0.3073 CCT = 1001K

EVERFINE




DC SPECTRUM DISTRIBUTION

CIE1931Chromaticity Diagram




CIET 95 TOMONIATION DIAGIAN



CERTIFICATIONS





SPECIFICATIONS

Charging time	24h
Voltage	120 - 277V
DC charging voltage	3.6V
AC charging current (max)	32mA
Discharge time	≥ 90mins
Luminous flux AC	10.139 lm
Luminous flux DC	326 lm
Color temperature	5500K ± 500K
Swiveling flood lights	350°/ 350°
Fire resistant	Yes
Suitable for Damp Locations Ingress	Yes
Included battery	Yes
Backup battery	90min
Battery built-in	3.6V1000mAh Ni-MH
Weight	2.18lbs
Warranty	3 years
Frequency	60Hz

Installation Options:

1. Single-Sided Sign - Mount sign with mounting points on back or top of the fixture.

2. Double-Sided Sign - Mount sign to the ceiling from mounting point on top of the fixture.

NOTE: You will find the mounting hardware stored inside the fixture for shipping purposes.