




4" SELECTABLE RETROFIT LED

Installation Manual


COMPONENTS








EASY INSTALLATION



- Turn off power at fuse or circuit breaker before installing.
- 2. Locate recessed can in ceiling. Remove existing light fixture.
 - Allow time for fixture to cool before removing.
- 3. Ensure the opening is 4" wide.



- Determine type of connector available in your recessed can.
 - TP24 Connector
 - E26 Base



- Connect appropriate adapter (E26 or TP24) to the retrofit light.
 - NOTE: Ensure all wires are attached to connectors.
- 6. Turn on power and test light.



- Slide CCT switch on retrofit to choose from 5 color temperature options.
 - Turn off light switch and continue install.



- 8. Tuck all wires into can.
- 9. Line up trim with opening in ceiling.
- Push light into can until secure. Spring clips will hold light in place.



 Turn on circuit breaker and test light.

WARNING

To reduce the risk of fire, electric shock, or physical injury:

- This product should be installed by a person familiar with the construction and operation
 of the product and the hazards involved.
- Abide by related regional and local laws or regulations.
- Check for shipping damage prior to install. If the product is damaged, do not use it.
- Do not alter, relocate, or remove fixture wiring. Do not make or alter any open holes in enclosure or electrical components.
- Turn off the switch and circuit breaker before installing this light fixture.
- Proper grounding is required to ensure safety.
- · This fixture is not suitable for wet environments.
- This fixture should not be installed directly over a heat source, on a radiant heating ceiling, or on the surface of combustible material, nor should this light be covered by flammable material
- Use safety precautions. Safety eyeglasses and gloves are recommended.

SPECIFICATIONS

Voltage	120
Wattage	11
Moisture Rating	Damp
Housing Material	Aluminum + PC
Weight	0.33 lbs
Warranty	7 years