

# ALTA VANITY LIGHT TUNABLE WHITE

## Install Guide and Manual



### COMPONENTS



**X1**  
Back Plate



**X3**  
Wire Nuts



**X2**  
Mounting Screws




**X2**  
Fixture Screws

### EASY INSTALLATION J-BOX MOUNTING


### OPERATION

Control color temperature options with the light switch.  
Choose from 3000K, 4000K, 5000K.


1. Turn on the light.
2. Flip the switch OFF then ON (in less than 3 seconds) repeatedly until you reach the desired CCT.
3. Your favorite color temperature is now locked in place.
4. Want to change it? Repeat these quick steps.




- Turn Power OFF
1. Turn off power at fuse or circuit breaker before installing or servicing.
  2. Remove fixture screws from canopy assembly.
  3. Remove back plate.




4. Pull all wires (live, neutral, ground) out of junction box (not included).
5. Mount the back plate to J-box with mounting screws, as shown.



6. Wrap the supply ground wire around the ground screw (on back plate). Tighten the screw. Leave 2 to 3 inches excess wire. Connect supply ground and fixture ground wires with wire nut.
  - If supply does not include ground wire, connect fixture ground to ground screw on back plate.



7. Connect remaining supply wires to fixture wires with included wire nuts.
  - Live to Black
  - Neutral to White
8. Tuck wires into J-box.
9. Tighten 2x fixture screws to back plate brackets to secure fixture to the wall.



10. Once secured, unthread/loosen the 2x screw caps. Move the lamp into desired position. Tighten the screw caps.



11. Turn on power.
12. If needed, rotate lamp position to redirect light beam.

### WARNING

- To reduce the risk of fire, electric shock or injury to people:
- This product should be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
  - Abide by related regional and local laws or regulations.
  - Proper grounding is required to ensure safety. Mount to a grounded junction box.
  - Turn off the switch and circuit breaker before installing this LED light fixture.
  - Use safety precautions. Safety eyeglasses and gloves are recommended.
  - Only connect this fixture to a 120V, 60 Hz power source. Connecting to a different power source may create a hazard and will void the warranty.
  - Do not use near or around flammable/combustible materials or liquids.
  - The bulb and unit can get hot during use. Turn off the power and allow the unit to cool for at least 20 minutes before working on the unit.
  - Do not attempt to open the fixture housing. There are no serviceable parts inside.
  - Check for damage during shipping prior to install. If the product is damaged, do not use it.
  - Please review instructions carefully before proceeding.

### SPECIFICATIONS

Voltage	120V
Wattage	15W
Lumens	1100
Suitable for Locations Ingress	Damp
Housing	Stainless steel
Warranty	5 years