


LINEAR HIGH BAYS 2FT

Install Guide and Manual

COMPONENTS




EASY INSTALLATION Chain Mounting


Required Tools: Drill, Ladder, Pliers, Tape Measure, Pencil.




1. Turn off power at fuse or circuit breaker before installing or servicing.



3. Insert hook ends into slotted holes, as shown.
• Repeat with second hook.




5. Secure fixture to ceiling by looping chain onto screw eye hooks.



8. Insert the terminal cap and wires into the driver box. Secure terminal cap.
9. Turn on power and test the light.


Turn Power ON




2. Hook chain onto 1x V hook.
• Repeat with second hook and chain.



4. Attach 2x anchors (not included) to the ceiling. Space the hooks 23.43 inches (595mm) apart.
• Screw eye hooks (not included) into the anchors.



6. After the installation, connect the supply wires in terminal cap to fixture wires. Refer to wiring instruction in diagram at left.
• Ground to Ground (yellow/green);
• Live to Live (black);
• Neutral to Neutral (white).
• Gray and Purple wires connect to dimmer. See DIMMING OPTIONS.



DIMMING OPTIONS
Gray and Purple wires connect to dimmer.
• Constant current can be achieved by 1-10V dimming. To make the lamp dimmable, connect to a compatible dimmer (not included) to the fixture's dimming signal wires.
• If you choose not to use the dimming function, cap each dimming wire (not together).

WARNING

- To reduce the risk of fire, electric shock or injury to people:
- This product should be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
 - Abide by related regional and local laws or regulations.
 - Proper grounding is required to ensure safety.
 - Do not cover the fixture with thermally insulating material.
 - Check for damage during shipping prior to install. If the product is damaged, do not use it.
 - Turn off the switch and circuit breaker before installing this LED light fixture.
 - Keep fixture away from corrosive substances. Keep the fixture dry and clean.
 - To ensure efficient light, regularly clean the light panel. Do not clean with harsh solvents.
 - Use safety precautions. Safety eyeglasses and gloves are recommended.
 - Please review instructions carefully before proceeding.

SPECIFICATIONS

Voltage	120-277V			
Wattage	80W	110W	160W	220W
Lumens	11,200	15,400	22,400	30,800
Weight	6.85lbs	6.85lbs	9.05lbs	10.7lbs
Suitable for Locations Ingress	Dry/Damp			
Warranty	10 years			