

REMODEL 6" LED CAN AIRTIGHT IC HOUSING

Quickly install the direct wire Remodel Can 6" with its included J-Box and TP25 connectors. The IC rated unit installs in your ceiling, surrounded by insulation. It is airtight to prevent A/C or heating leaks through the housing. Add any 6" retrofit downlight LEDs to this can. TP24 Connector and J-Box included.

MODELS

SUN-6RM/IC SUN-6RM/IC10PK
SUN-6RM/IC4PK SUN-6RM/IC12PK

FEATURES

IC Rated

Airtight

CONSTRUCTION

Housing	Aluminum
Remodel Bar/Bracket	Galvanized Steel
Junction Box	Galvanized Steel
Rivet	Plated Steel
"C" Clip	Galvanized Steel
Ideal Connector # 30-682M (Male)	Plastic & Copper
Remodelling Clip	Painted Steel
Weight	1.2lbs

Sunco is proudly based in the USA, offering quality products at affordable prices and knowledgeable support specialists.



SPECIFICATIONS

Voltage **120V/277V**

Max. Wattage Accepted **24W**

Ceiling Thickness

Housing adjusts from 5/8"-1' 3/8" to accommodate various ceiling thickness

Junction Box

Listed for through branch circuit wiring

Contains one 1-1/8" knockout, six 7/8" knockouts, and four Romex pryouts with strain relief

Remodel Clips

Four remodel clips should secure and accommodate 1/2" and 5/8" ceiling materials

Environment

Operating Temperature **Max 194°F**

Suitable for Locations Ingress **Wet & Damp**

Lifespan

Warranty **5 years**

CERTIFICATIONS

