LEDone®



2 Foot 20W / 25W / 30W

OPTIONAL ACCESSORIES:



Emergency Back-up

LED Multi Wattage Multi CCT Vapor Tight Light Family Series

CONSTRUCTION:

PC housing and white cover.

OPTICAL SYSTEM:

Seoul 2835 LED chips. 110° beam angle.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

120-277V input standard. -20°C to 40°C, -4°F to 104°F

INSTALLATION & MOUNTING:

Surface mount.

CONTROLS & DIMMING:

0-10V dimming comes standard.







FEATURES

- Default Wattage:
 - o 8FT 100W
 - o 4FT 50W
 - o 2FT 30W
- Default CCT: 5,000K
- IP65 rated
- NSF rated for splash zone and nonfood zone
- UL 1598 suitable for wet location
- 50,000 hours lifetime

SUITABLE APPLICATIONS

- Warehouses
- Factories
- Garage
- Parking lot

LED Multi Wattage Multi CCT Vapor Tight Light Family Series

LOC-2FTTPVT-MW-CCT-D								
WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
20W	3500K / 4000K / 5000K	2,264LM	113.2LM/W	120-277V	80	0.9	20%	
25W	3500K / 4000K / 5000K	2,830LM	113.2LM/W	120-277V	80	0.9	20%	
30W	3500K / 4000K / 5000K	3,396LM	113.2LM/W	120-277V	80	0.9	20%	

MEASUREMENTS

2FT

