

2FT Multi Wattage Multi CCT Vapor Tight Light



2 Foot

20W / 25W / 30W

SUITABLE APPLICATIONS

- Warehouses
- Schools
- Factories
- Offices
- Supermarkets
- Logistic Centers
- Exhibition Halls

CONSTRUCTION:

PC housing and white cover with stainless steel clips.

OPTICAL SYSTEM:

Lumiled 2835 LED chips. 110° beam angle.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

120-277V input standard.
-4°F to 104°F

INSTALLATION & MOUNTING:

Surface mount or suspension mount.

CONTROLS & DIMMING:

0-10V dimming comes standard. Suitable for use with LED dimmers. Auxiliary 12V output.

FEATURES

- Default Wattage:
 - 2FT – 30W
- Default CCT: 5,000K
- IK10 & IP66 rating
- NSF rated for splash zone and nonfood zone
- Glare-free / flicker-free lighting
- Linkable design (see page 2 for details)
- 100,000 hours lifetime



MOUNTING OPTIONS:



Surface Mount

OPTIONAL ACCESSORIES:



Emergency Back-up



Sensor



Remote Control

LOC-2FTVT-MW(20/25/30)MCCT(35/40/50)

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
20W	3500K / 4000K / 5000K	2,738LM	136.91LM/W	120-277V	81.7	0.9049	15.76%	(2) 17W LED tubes
25W	3500K / 4000K / 5000K	3,422LM	136.91LM/W	120-277V	81.7	0.9049	15.76%	(2) 17W LED tubes
30W	3500K / 4000K / 5000K	4,086LM	136.91LM/W	120-277V	81.7	0.9049	15.76%	(2) 32W LED tubes

LINKING TOGETHER

Model Number	Voltage (18AWG)	Linkable Qty	Voltage (16AWG)	Linkable Qty
LO-LOC-2FTVT-MW-MCCT	120V	30	120V	45
	240V	60	240V	90
	277V	70	277V	110

MEASUREMENTS

