

# LED 4FT Multi Wattage Multi CCT Vapor Tight High Bay Light



**4FT**

60W, 75W and 90W



## CONSTRUCTION:

PC housing and white cover with stainless steel clips.

## OPTICAL SYSTEM:

Lumiled 2835 LED chips. 110° beam angle.

## WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

## ELECTRICAL:

120-277V input standard.  
-4°F to 104°F

## INSTALLATION & MOUNTING:

Surface mount or suspension mount.

## CONTROLS & DIMMING:

0-10V dimming comes standard. Suitable for use with LED dimmers. Auxiliary 12V output.

## FEATURES

- Default Wattage:
  - 4FT – 90W
- Default CCT: 5,000K
- IK10 & IP65 rating
- Dust-tight
- NSF rated for splash zone and nonfood zone
- Auxiliary 12V output
- Linkable design (see page 2 for details)
- 100,000 hours lifetime

## SUITABLE APPLICATIONS

- Food / beverage factories
- Heavy manufacturing facilities
- Underground parking
- Refrigerated storage room
- Warehouse
- Tunnel



## MOUNTING OPTIONS:



Surface Mount

## OPTIONAL ACCESSORIES:



Emergency Back-up



Sensor



Remote Control

# LED 4FT Multi Wattage Multi CCT Vapor Tight High Bay Light

LO-LOC-4FTVTHB-MW-607590-MCCT-354050

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
60W	3500K / 4000K / 5000K	8,916LM	148.6lm/W	120-277V	80	0.9	20%	(4) 32W LED tubes
75W	3500K / 4000K / 5000K	11,145LM	148.6lm/W	120-277V	80	0.9	20%	(4) 32W LED tubes
90W	3500K / 4000K / 5000K	13,374LM	148.6lm/W	120-277V	80	0.9	20%	(4) 32W LED tubes

## LINKING TOGETHER

Model Number	Voltage (18AWG)	Linkable Qty	Voltage (16AWG)	Linkable Qty
LO-LOC-4FTVTHB-MW-607590-MCCT-354050	120V	10	120V	15
	240V	20	240V	30
	277V	24	277V	35

## MEASUREMENTS

