LEDone®

LED 3 Multi Wattage Multi CCT 4 Foot Wrap

Around Light

FEATURES

Default Wattage: 48W

Default CCT: 5,000K

IP20 rated

• 50,000 hours lifetime

CONSTRUCTION:

22-gauge metal housing with matte white finish. PMMA cover lens.

OPTICAL SYSTEM:

Samsung 2835 LED chips. Frosted lens. 110° beam angle.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

Available as 120-277V input.

Operating Temperature: -4°F to 122°F

INSTALLATION & MOUNTING:

Suspension or surface mounting options.

CONTROLS & DIMMING:

0-10V dimming comes standard.



32W / 40W / 48W

SUITABLE APPLICATIONS

- Distribution Centers
- Aisles
- Corridors
- Restrooms
- Commercial Facilities
- Warehouses
- Stairwells
- Hallways







Suction cup to assist in lifting wrap cover included

LED 3 Multi Wattage Multi CCT 4 Foot Wrap Around Light

LO-LOC-4FWA-MW-48-MCCT-D								
WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
32W	3500K / 4000K / 5000K	3,680LM	115LM/W	120-277V	81.6	0.969	17.2%	
40W	3500K / 4000K / 5000K	4,600LM	115LM/W	120-277V	81.6	0.969	17.2%	
48W	3500K / 4000K / 5000K	5,814.72LM	120.5LM/W	120-277V	81.6	0.969	17.2%	

MEASUREMENTS





