

# LEDone®

## LED Foldable Linear High Bay Family Series

### FEATURES

- Default Wattage:
  - 110W
- Foldable sides
- IP40 rated
- DC 12V auxiliary
- Easy installation and maintenance
- 50,000 hours lifetime



70W / 90W / 110W

### CONSTRUCTION:

Die formed galvanized steel, white paint.  
Isolated driver with wide voltage input option.  
Frosted PMMA lens. (Clear lens special order)

### OPTICAL SYSTEM:

Lumileds 2835 LED chips. 120° beam angle options.

### WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

### ELECTRICAL:

Available as 120-277V input.  
Operating Temperature: -4°F to 104°F

### INSTALLATION & MOUNTING:

Hanging hook or pendant mount.

### CONTROLS & DIMMING:

0-10V dimming comes standard. Suitable for use with LED dimmers.

### SUITABLE APPLICATIONS

- Warehouses
- Factories
- Supermarkets
- Logistic Centers
- Exhibition Halls

### MOUNTING OPTIONS:



Pendant Mount



Chain & Hook



## LED Foldable Linear High Bay Family Series

### LO-LOC-2FTFLHB-MW-110-50KD

WATTAGE SELECTABLE	CCT	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
70W	5000K	10,640LM	152lm/W	120-277V	80	0.9	20%	400W HID
90W	5000K	13,680LM	152lm/W	120-277V	80	0.9	20%	400W HID
110W	5000K	16,720LM	152lm/W	120-277V	80	0.9	20%	400W HID

# FOLDABLE STYLE

LEDone®



# MEASUREMENTS

LO-LOC-2FTFLHB-MW-110-50KD

