

# LEDone®

## LED Foldable Linear High Bay Family Series

### FEATURES

- Default Wattage:
  - 175W
- Foldable sides
- IP40 rated
- DC 12V auxiliary
- Easy installation and maintenance
- 50,000 hours lifetime



145W / 160W / 175W

### CONSTRUCTION:

Die formed galvanized steel, white paint. Isolated driver with wide voltage input option. Frosted PMMA lens. (Clear lens special order)

### OPTICAL SYSTEM:

Lumileds 2835 LED chips. 120° beam angle options.

### WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

### ELECTRICAL:

Available as 120-277V input. Operating Temperature: -4°F to 104°F

### INSTALLATION & MOUNTING:

Hanging hook or pendant mount.

### CONTROLS & DIMMING:

0-10V dimming comes standard. Suitable for use with LED dimmers.

### SUITABLE APPLICATIONS

- Warehouses
- Factories
- Supermarkets
- Logistic Centers
- Exhibition Halls

### MOUNTING OPTIONS:



Pendant Mount



Chain & Hook



## LED Foldable Linear High Bay Family Series

### LO-LOC-2FTFLHB-MW-175-50KD

WATTAGE SELECTABLE	CCT	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
145W	5000K	22,040LM	152lm/W	120-277V	80	0.9	20%	400W – 600W HID
160W	5000K	24,320LM	152lm/W	120-277V	80	0.9	20%	400W – 600W HID
175W	5000K	26,600LM	152lm/W	120-277V	80	0.9	20%	400W – 600W HID

# FOLDABLE STYLE

LEDone®



# MEASUREMENTS

LO-LOC-2FTFLHB-MW-175-50KD

