

LEDone[®]

LED Foldable Linear High Bay Family Series

FEATURES

- Default Wattage:
 - 440W
- Foldable sides
- IP40 rated
- DC 12V auxiliary
- Easy installation and maintenance
- 50,000 hours lifetime



360W / 400W / 440W

CONSTRUCTION:

Die formed galvanized steel, white paint.
Isolated driver with wide voltage input option.
Frosted PMMA lens. (Clear lens special order)

OPTICAL SYSTEM:

Lumileds 2835 LED chips. 120° beam angle options.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

Available as 120-277V input.

Operating Temperature: -4°F to 104°F

INSTALLATION & MOUNTING:

Hanging hook or pendant mount.

CONTROLS & DIMMING:

0-10V dimming comes standard. Suitable for use with LED dimmers.

SUITABLE APPLICATIONS

- Warehouses
- Factories
- Supermarkets
- Logistic Centers
- Exhibition Halls



MOUNTING OPTIONS:



Pendant Mount



Chain & Hook



LED Foldable Linear High Bay Family Series

LO-LOC-4FTLHB-MW-440-50KD

WATTAGE SELECTABLE	CCT	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
360W	5000K	54,720LM	152lm/W	120-277V	80	0.9	20%	1400W – 1700W HID
400W	5000K	60,800LM	152lm/W	120-277V	80	0.9	20%	1400W – 1700W HID
440W	5000K	66,880LM	152lm/W	120-277V	80	0.9	20%	1400W – 1700W HID

FOLDABLE STYLE



MEASUREMENTS

LO-LOC-4FTLHB-MW-440-50KD

