

LEDone[®]

LED Foldable Linear High Bay Family Series

FEATURES

- Default Wattage:
 - 350W
- Foldable sides
- IP40 rated
- DC 12V auxiliary
- Easy installation and maintenance
- 50,000 hours lifetime



290W / 320W / 350W

CONSTRUCTION:

Die formed galvanized steel, white paint.
Isolated driver with wide voltage input option.
Frosted PMMA lens. (Clear lens special order)

OPTICAL SYSTEM:

Lumileds 2835 LED chips. 120° beam angle options.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

ELECTRICAL:

Available as 120-277V input.

Operating Temperature: -4°F to 104°F

INSTALLATION & MOUNTING:

Hanging hook or pendant mount.

CONTROLS & DIMMING:

0-10V dimming comes standard. Suitable for use with LED dimmers.

SUITABLE APPLICATIONS

- Warehouses
- Factories
- Supermarkets
- Logistic Centers
- Exhibition Halls



MOUNTING OPTIONS:



Pendant Mount



Chain & Hook



LED Foldable Linear High Bay Family Series

LO-LOC-4FTLHB-MW-350-50KD

WATTAGE SELECTABLE	CCT	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
290W	5000K	44,080LM	152lm/W	120-277V	80	0.9	20%	1000W – 1,400W HID
320W	5000K	48,640LM	152lm/W	120-277V	80	0.9	20%	1000W – 1,400W HID
350W	5000K	53,200LM	152lm/W	120-277V	80	0.9	20%	1000W – 1,400W HID

FOLDABLE STYLE



MEASUREMENTS

LO-LOC-4FTLHB-MW-350-50KD

