

Item#: 26419 LED PLUG & GO™ LINEAR T8

REPLACEMENT LAMPS (PLUG AND PLAY) (UL TYPE A)

FEATURES

Our T8 LED tube can work with the most popular electronic ballasts that are capable of replacing your existing fluorescent T8 lamps without any additional wiring. It provides exceptional LED lighting with reduced energy and maintenance costs.

PLUG & GO™ - WORKS WITH EXISTING ELECTRONIC BALLAST*

- · Thermal fuse for added safety
- Exceptional efficacy
- No flickering
- *Suitable for use with Instant Start dimming ballasts. Not suitable for emergency ballasts.

ELECTRICAL

LLLOTIIIOAL			
Wattage	13W		
Voltage	120-277V		
Current	136-60mA		
Power Factor	0.9		
Total Harmonic Distortion (THD)	20		
LIGHTING PERFORMANCE			
Lumens	1600		
Lumens Per Watt (LPW)	123		
Color Temperature (CCT)	5000K		
Color Rendering (CRI)	80		
R9 (Red Value)	5		
R13 (Skin Tones)	82		
Beam Angle	180°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B1 - U1 - G1		
Dimmable Lighting Control	Compatible with select dimming ballasts.		
ENVIRONMENT			
Operating Temperature	-4° ~ 113°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP20		
Suitable Fixture Type	Enclosed		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	HL-A-2835HW-S1-08-HR3		
CONSTRUCTION			
Housing	Glass / Plastic End Caps		
Lens	Frosted		
Base / Power Supply	G13 - Medium Bi Pin		

QUALIFICATIONS






Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **26419 LED PLUG & GO™ LINEAR T8**

DIMENSIONS (Inches)

Length (MOL)	48"
Width/Diameter (MOD)	1"
Net Weight (Lbs)	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768029956	49.7" x 7.5" x 6.5"	11.6
Individual Box	1	811768029953	47.8" x 1.1" x 1.1"	0.46
Country of Origin	China			
HS Tariff	8539.50.0050			