

Item#: 64055 LED 2X4 TROFFER - 3 LAMP LED READY FIXTURE

FEATURES

- · Uses 30% less energy than a linear fluorescent troffer
- · Die formed, and rigidly fabricated
- Smooth edges for easy handling and no exposed fasteners
- Prismatic acrylic diffuser
- Door hinges are on either side for easy re-lamping
- Positive locking cam action latches with matching finish
- LED ready with non-shunted sockets
- Pre-wired at one end
- Exposed T-grid ceiling and recessed ceiling mount

APPLICATION

Ideal for offices, retail, commercial buildings and work areas.

ELECTRICAL

Lamp Type (not included)	Т8	
Number of Lamps	3	
Voltage	120-277V	
ENVIRONMENT		
Operating Temperature	-4° ~ 122°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP40	

LI	23)r	A	N

Warranty (Years) 2	2
--------------------	---

CONSTRUCTION

Housing	24 Gauge Steel		
Base / Power Supply	Hard Wired		
Finish	High Gloss Baked White Enamel		


QUALIFICATIONS



Operating temperature may vary depending on the lamps used. - Specifications are subject to change without notice.

DIMENSIONS (Inches)

Length	48"
Width	24"
Height	3.3"
Weight (Lbs)	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768025217	49.2" x 24.4" x 3.5"	18.7
Country of Origin	China			
HS Tariff	9405.10.6020			

ADDITIONAL INFORMATION:

• Pairs with Superior Life[®] Direct Wire Single-End or Double-End UL Type B Lamps. Single-end pre-wired fixtures can also be wired double-end by the end-user if needed. Follow specific lamp installation wiring instructions for correct wiring.