

Item#: 07838 LED TONE-SELECT™ DESIGNER SURFACE MOUNT

INDOOR FIXTURE

FEATURES

- · Selectable color temperature
- LED surface mount fixture provides glare free illumination and even light distribution with a clean, modern look.
- Diffusing lens
- · Low profile design
- Title 24 JA8 Compliant

APPLICATION

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, hallways, lobbies and other residential and commercial applications.

ELECTRICAL

Wattage	18W	
Voltage	120V	
Current	0.17A	
Power Factor	0.9	
LIGHTING PERFORMANCE		
Lumens	1350	
Lumens Per Watt (LPW)	75	
Color Temperature (CCT)	30K / 40K / 50K	
Color Rendering (CRI)	90	
R9 (Red Value)		
Beam Angle	120°	
Light Distribution	Type II, Very Short	
BUG Rating (Backlight, Uplight, and Glare)	B1 - U1 - G1	
Dimmable Lighting Control	Dimmable see compatibility report	
ENVIRONMENT		
Operating Temperature	-4° ~ 104°F	
Suitable Location	DAMP Indoor / Covered Ceilings	
Ingress Protection Rating	IP20	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	

COMPONENTS LED Light Source

Driver

CONSTRUCTION	
Housing	
Lens	
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS




Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

SMD 2835

Internal

Item#: 07838 LED TONE-SELECT $^{\text{m}}$ DESIGNER SURFACE MOUNT



DIMENSIONS (Inches)

Width/Diameter (MOD)	8.9"	
Height	0.5"	
Net Weight (Lbs)	1.2	

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	20	10811768029687	16.5" x 14.6" x 15.4"	30.9
Individual Box	1	811768029680	9.6" x 9.1" x 1.3"	1.5
Country of Origin	China			
HS Tariff	9405.99.4090			