

# LEDone®

## LED Multi Watt Multi CCT Troffer Family Series

### FEATURES

- Default Wattage:
  - 2x2 – 29W
- Default CCT: 5,000K
- Glare-free lighting
- IP20 rated
- 100,000 hours lifetime

### CONSTRUCTION:

Steel and Aluminum frame. Matte white finish. The entire fixture functions as a heat sink to keep the LEDs cooler to prolong the life of the light.

### OPTICAL SYSTEM:

Samsung 2835 LED chips. 110° beam angle.

### WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

### ELECTRICAL:

120-277V input standard.  
Operating Temperature: -4°F to 122°F

### INSTALLATION & MOUNTING:

Fits most preexisting troffers. Surface mount kit.

### CONTROLS & DIMMING:

0-10V dimming comes standard. Suitable for use with LED dimmers.



2x2


15W, 19W, 24W and 29W

### SUITABLE APPLICATIONS

- Warehouses
- Schools
- Factories
- Offices
- Supermarkets
- Logistic Centers
- Exhibition Halls



### MOUNTING OPTIONS:



Surface Mount

## LED Multi Watt Multi CCT Troffer Family

### LO-LOC-22TROF-DMWMCCT

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
15W	3500K / 4000K / 5000K	1,942.5LM	129.5lm/W	120-277V	80	0.9	20%	150W HID
19W	3500K / 4000K / 5000K	2,460.5LM	129.5lm/W	120-277V	80	0.9	20%	150W HID
24W	3500K / 4000K / 5000K	3,108LM	129.5lm/W	120-277V	80	0.9	20%	150W HID
29W	3500K / 4000K / 5000K	3,755.5LM	129.5lm/W	120-277V	80	0.9	20%	150W HID

# MEASUREMENTS

LEDone®

2x2

