ISO

Item#: 78655

LED 8' SPEC-SELECT™ VAPOR TIGHT

DIRECT LINEAR AMBIENT LUMINARIES

SELECTABLE **WATTAGE & CCT** INTEGRATED SENSOR OPTION

FEATURES

Spec-Select™ Vapor Tights are like 9 fixtures in 1, featuring adjustable wattage and color temperature for the perfect balance of light in any application.

· Adjustable Wattage (3 settings)
· Adjustable Color (3 settings)
· Integrated Sensor Option (ISO). Sensor and elbow sold separately.
· 5VA housing, meets highest UL94 Standards.
· Liquid silicone perimeter gasket formed to housing provides a seamless seal and protects from dust and humidity.
· Stainless steel clips.
· Sufficient knockouts are available.

APPLICATION

Ideal for commercial and industrial environments; tunnels, stairwells, parking garages, cold storage, and airports. *Not designed for use in car washes, truck wash bays, or where exposed to harsh chemicals.*

ELECTRICAL

Wattage	65W / 75W / 90W
Voltage	120-277V
Current	90W @ 120V = 0.75A
Power Factor	0.9
Total Harmonic Distortion (THD)	7.1

LIGHTING PERFORMANCE

Lumens	8645 / 9975 / 11970
Lumens Per Watt (LPW)	133
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	82
R9 (Red Value)	7
Beam Angle	120°
Light Distribution	--
Dimmable Lighting Control	From optional 12VDC sensor, or customer 0-10V controls.

ENVIRONMENT

Operating Temperature (Suspended at least 18" from ceiling)	-40° ~ 113°F
Operating Temperature (Surface Mount)	-40° ~ 104°F
Suitable Location	WET
Ingress Protection Rating	IP65

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	**5**

COMPONENTS

LED Light Source	--
Driver	--
Sensor Socket	12VDC AUX.

CONSTRUCTION

|	
Housing	Polycarbonate
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

UL CERTIFIED   DLC LISTED

Visit www.designlights.org/search to confirm qualification. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

Item#: **78655**
LED 8' SPEC-SELECT™ VAPOR TIGHT

94.5"

3.8"

3.1"

DIMENSIONS (Inches)

Length	94.5"
Width	3.8"
Height	3.1"
Net Weight (Lbs)	7.9

PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10811768029885	96.7" x 8.5" x 7.5"	--
Individual Box	1	811768029888	95.8" x 3.9" x 3.4"	--
Country of Origin	China			
HS Tariff	--			

ADDITIONAL INFORMATION:

- Default settings; 65W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. The color temperature and wattage should be selected prior to installation.

CCT Switch   Wattage Switch