



Item#: **16755**
LED 2' SPEC-SELECT™
DESIGNER STRIP
 DIRECT LINEAR AMBIENT LUMINARIES

FEATURES

Spec-Select™ Designer Strips are like 9 fixtures in 1, featuring adjustable wattage and color temperature for the perfect balance of light in any application.

- Adjustable Wattage (3 settings)
- Adjustable Color (3 settings)
- Integrated Sensor Option (ISO). Sensor and elbow sold separately.
- Easy installation.

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	15W / 20W / 25W
Voltage	120-277V
Current	25W @ 120V = 0.20A
Power Factor	0.9
Total Harmonic Distortion (THD)	14.1

LIGHTING PERFORMANCE

Lumens	1980 / 2640 / 3300
Lumens Per Watt (LPW)	132
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	83
R9 (Red Value)	6
Beam Angle	130°
Light Distribution	Type II, Very Short
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1
Dimmable Lighting Control	From optional 12VDC sensor, or customer 0-10V controls.

ENVIRONMENT

Operating Temperature	-4 ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Bridgelux
Driver	SIF30-I0550-SS
Sensor Socket	12VDC AUX.

CONSTRUCTION


Housing	Aluminum
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS



Item#: **16755**
LED 2' SPEC-SELECT™ DESIGNER STRIP

ITEM INFORMATION



DIMENSIONS (Inches)

Length	22.2"
Width	1.9"
Height	2.5"
Net Weight (Lbs)	--

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	6	10811768026396	23.2" x 6.8" x 8.4"	--
Individual Box	1	811768026399	22.7" x 2.2" x 2.7"	--
Country of Origin	China			
HS Tariff	--			

ADDITIONAL INFORMATION:

- Default settings; 15W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. For additional information refer to the install instructions.

