

Item#: 14819
LED TONE-SELECT™ DUAL
POWER LINEAR T5
INTERNAL DRIVER LAMP-STYLE
RETROFIT KITS (UL TYPE B)

## **FEATURES**

The LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

# SINGLE OR DOUBLE ENDED DIRECT WIRE

- Adjustable color temperature (3 Settings)
- · No ballast required, lamp runs off main
- · Exceptional efficacy
- Suitable for both Shunted and Non-Shunted Sockets

(Review install instructions for more details.).

#### **ELECTRICAL**

Wattage	16W	
Voltage	120-277V	
Current	140mA	
Power Factor	0.9	
Total Harmonic Distortion (THD)	20	

#### **LIGHTING PERFORMANCE**

Lumens	2050 / 2100 / 2100		
Lumens Per Watt (LPW)	130		
Color Temperature (CCT)	3500K / 4000K / 5000K		
Color Rendering (CRI)	83		
R9 (Red Value)			
R13 (Skin Tones)	<del></del>		
Beam Angle	180°		
BUG Rating (Backlight, Uplight, and Glare)			
ENVIRONMENT			
Operating Temperature	-4° ~ 113°F		
	D 111D		

operating temperature	-4° ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Suitable Fixture Type	0pen	
Suitable for Emergency Fixtures	No	

#### LIFESPAN

Average Life (Hours)	50,000	
Warranty (Years)	5	

## **COMPONENTS**

LED Light Source	Samsung

### **CONSTRUCTION**

Housing	Glass / Plastic End Caps		
Lens	Safety Coated		
Base / Power Supply	G5 - Mini Bi Pin		


## **QUALIFICATIONS**



Published lumens on LED products are approximate and may vary slightly. Specifications are subject to change without notice.

# Item#: 14819

# LED TONE-SELECT™ DUAL POWER LINEAR T5



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Net Weight (Lbs)				
Width/Diameter (MOD)	0.8"			
Length (MOL)	34"			
DIMENSIONS (Inches)				

PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	<b>GROSS WEIGHT</b> (Lbs)
Master Carton	25	10811768027201		
Individual Box	1	811768027204		
Country of Origin	China			
HS Tariff	8539.52.0051			

## **ADDITIONAL INFORMATION:**

Safety Feature: Tube(s) will not light if power is still running through the ballast. Refer to the install instructions for proper installation.