

DOCK315EUZ



What's in the Box:

- UK and EU AC power cords 1.8 m
- Quick Start Guide
- AC Adapter, AC to DC output 20 V, 5 A, 100 W
- DOCK315
- 1 m USB-C to USB-C Cable with screw mount and USB-C to USB-A tether adapter







Targus® Universal USB-C Dual 4K DisplayPort Docking Station with 65W Power Delivery

D I-		4	4	4
DOCK	connection	type to	nost	aevice

Connector type	USB-C / USB-A via adaptor (included)	
Connector technology	USB 3.2 Gen 2	
Graphics Technology	DisplayLink	
Host port compatibility		
USB 3	•	
USB 4	•	
Thunderbolt 3	•	
Thunderbolt 4	•	

Video norte

video ports			
HDMI			
Display Port	2		
VGA			
Video via High-speed USB / Thunderbolt port			
Maximum no. of monitor(s)	2		
Maximum resolution (single monitor)	5K		
Maximum resolution (multi-monitor)	2 x 4K @ 60 Hz		
HDR via HDMI			

USB-A (Max data speed)	3 (4.5 W per port / 5 Gbps)
USB-C (Power Delivery / Max data speed)	2 - 1 to host (65 W PD / 10 Gbps), 1 (7.5 W / 10 Gbps)
Thunderbolt 3	
Thunderbolt 4	
RJ45 Ethernet	Gigabit Ethernet
3.5 mm Audio	•
Other audio ports	
Memory cards	

when host device is connected using USB-C via included cable to DOCK's USB-C [to host] PD port only*

Legacy laptop power connectors Max. power pass-thru / Max. power delivery to host

Power required for operation and charging

No Guaranteed up to 65 W to host device

100 W Power adapter included

Host system OS compatibility Works with Windows®

WORS WILL WILLOWS	•	
Works with MacOS®	•	
Works with ChromeOS®	•	
Works with iOS®		
Works with Android®	•	
Works with Samsung DEX		
Works With Linux Ubuntu™	•	

Device compatibility Windows® Laptop

Microsoft Surface® Laptop
ChromeBook®
Apple iMac®
Apple MacBook Pro® / Air® 2016 - 2019
Apple MacBook Pro® / Air® M1 / M2 2020 - 2022 Apple MacBook Pro® M1 / M2 Pro / Max 2021 - 2023 Apple iPad Air® 2020 or later Apple iPad Air® 2020 or later Android® Tablet Android® Smartphone
•

Targus MiraLogic™ features

Auto discover peripherals	
Auto inventory peripherals	
Remote IT management	
Data security	
Bluetooth® Mesh network	
MiraLogic™ Smart Sensor	
MiraLogic™ Smart Power Strip	

Other features

On/ On Switch	
PXE Boot	
Wake-on LAN	
LAN/ WLAN Switching	
Mac Address passthru	
Security cable lock slot	
Compatible cable locks	• - Targus

- Aluminium/ metal alloy construction VESA mount compatible USB-C [to host device] port screw mount
- - Targus PA410 series, ASP9 series
- - Targus ACX003GLZ • - Compatible with Targus ACC1133GLX, ACC1135GLX

3 years

Dimensions

Length x Width x Height (cm)	16.6 x 8.3 x 3.0 cm
Weight (kg)	0.3 Kg