

HyperDrive[•] Next

HD7001GL Business Class 10 Port USB-C Docking station

LOBEC LOOW PD 3.0 USB-C LOGEPS USB-C LOGEN USB-C LOGEN

Dimensions:

Length x Width x Height (cm) – 17.0 x 8.3 x 1.7 cm Weight (kg) - Approx. 0.240 Kg (USB-C cable – 9 g) SRP: £179.99| €199.99

Product Specification – HD7001GL

USB-C* - via USB-C to USB-C cable included USB 3.2 Gen 2 (10 Gbps) Hybrid - DP Alt Mode + SiliconMotion® USB Graphics • •
Hybrid - DP Alt Mode + SiliconMotion® USB Graphics •
Graphics
•
:
•
1x HDMI 2.0 - DP Alt mode 1x HDMI 1.4 - USB Graphics
2
4K @ 60 Hz via DP Alt Mode
4K @ 30 Hz via USB Mode**
4K @ 60 Hz + 4K @ 30 Hz**
2x USB 3.2 Gen2 (10 Gbps)
1x USB 3.2 Gen2 (100 W PD / 10 Gbps) to
host
1x USB 3.2 Gen2 (10 Gbps)
1x USB PD 3.0 (Max. 100 W)
 Gigabit Ethernet
Gigabit Ethernet
SD/ MicroSD 4.0 (312 MB/s) - UHS-II card
compatible*****
•
 when hub is connected to optional USB-C PD 3.0 charger or HJ8003 AC adapter***
USB-C PD 3.0 charger- 100 W PD 3.0 / up to
85 W pass through to host device
ss w pass through to nost device
HJ8003 AC adapter - 150 W adapter /
guaranteed up to 100 W to host device
•
•
•

Host system OS compatibility	
Works with Windows®	•
Norks with MacOS [®]	•
Works with ChromeOS®	•****
Works with iOS®	
Works with Android®	
Works with Samsung DEX	
Works With Linux Ubuntu™	
Device compatibility	
Windows® Laptop	•
Microsoft Surface [®] Laptop	•
ChromeBook®	•
Apple iMac®	
Apple MacBook Pro® / Air® 2016 - 2019	•
Apple MacBook Pro [®] / Air [®] M1 / M2 2020 - 2022	•
Apple MacBook Pro® / M1 / M2 Pro / Max 2021 - 2023	•
Apple iPad Pro [®] 2018 or later	
Apple iPad Air [®] 2020 or later	
Android® Tablet	
Android [®] Smartphone	
Other features	
Dn/ Off Switch	•
PXE Boot	•*****
Wake-on LAN	•
LAN/ WLAN Switching	•*****
Mac Address passthru	•*****
Security cable lock slot	1x Kensington® standard K slot 1x Kensington® Nano slot
Compatible cable locks	 Targus ASP9 series Universal lock
Construction material	Up to 85% PCR recycled plastics where applicable
/ESA mount compatible	-
JSB-C [to host device] cable	Detachable USB-C to USB-C cable (included)
Warranty	2 years
Content	
	 HD7001GL Business Class 10 port USB-C
What's in the box	Docking Station
	 USB-C to USB-C cable User Guide
Notes 'Full hub data, video and power functionality will require host device with USB-C port compatible with DP Alt Mode,	Preser Delivery DD 2 0 and 159 2 3 Gen1 / Gen2
Trafl hub data, sideo and power buckdowsky will require host or with USE C port compatible with USA M host or with USE C port compatible with USA M host or with USE C port compatible with USA M host or set portion of the USA M host or set portion of the USA M host or set hash host Host or more with both HOST M host or set portion of the USA P requires C more also with the USA M host or set hash host the USA M host or set hash host or set hash host host or set hash host or set to use has a set hash host or set or set hash host or host or host or host or set hash host or hos	/iew driver download from http://www.siliconmotion.com/downloads/index.html. Single /li ports on docking station are connected to compatible external monitors adapter HJ8003

Prices, dates, features, and specifications are subject to change without notice. Many Hyper products have been granted patents. See targus.com/patents for details. ©2023 Hyper. Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries. iPad and Mac are trademarks of Apple Inc., registered in the US and other countries. All trademarks and registered trademarks are the property of their respective owners.