



HyperDrive Next


HD7002GL Dual 4K HDMI 7 port USB-C Hub

Dimensions:

Length x Width x Height (cm) $-12.5 \times 6.7 \times 1.8 \text{ cm}$

Weight (kg) - Approx. 0.180 Kg

SRP: £139.99 | €149.99



Product Specification – HD7002GL

onnection to host device		Host system OS compatibility	
Connector type	USB-C*	Works with Windows®	•
onnector technology	USB 3.2 Gen 2 (10 Gbps)	Works with MacOS®	•
Graphics Technology	Hybrid - DP Alt Mode + SiliconMotion®	Works with ChromeOS®	•***
	USB Graphics	Works with iOS®	● * * * * * ·
		Works with Android®	•****
lost device port compatibility		Works with Samsung DEX	
SB 3	•	Works With Linux Ubuntu™	
SB4	•		
hunderbolt 3	•	Device compatibility	
hunderbolt 4	•	Windows® Laptop	•
		Microsoft Surface® Laptop	•
'ideo ports		ChromeBook®	•
	1x HDMI 2.0 - DP Alt mode	Apple iMac [®]	
IDMI	1x HDMI 1.4 - USB Graphics	Apple MacBook Pro® / Air® 2016 - 2019	•
Display Port		Apple MacBook Pro® / Air® M1 / M2 2020 - 2022	•
/GA		Apple MacBook Pro® / M1 / M2 Pro / Max 2021 - 2023	•
/ideo via High-speed USB / Thunderbolt port		Apple iPad Pro® 2018 or later	_****
Maximum no. of monitor(s)	2	Apple iPad Air® 2020 or later	****
• •	4K @ 60 Hz via DP Alt Mode	Android® Tablet	*****
Maximum resolution (single monitor)	4K @ 30 Hz via USB Mode**		*****
Maximum resolution (multi-monitor)	4K @ 60 Hz + 4K @ 30 Hz**	Android® Smartphone	• *****
HDR via HDMI		Other features	
		Other readures	
Connection Ports		Construction material	Up to 85% PCR recycled plastics where applicable
JSB-A (Power / Max data speed)	1x USB 3.2 Gen2 (10 Gbps)	VESA mount compatible	аррисамс
USB-C (Power / Max data speed)	2x USB 3.2 Gen2 (10 Gbps)	•	
	1x USB PD 3.0 (Max. 100 W)	USB-C cable to host device	Built in cable
	1X 03B FD 3.0 (Wax. 100 W)	Warranty	2 years
hunderbolt 3			
hunderbolt 4		Content	
J45 Ethernet	Gigabit Ethernet		HD7002GL Dual 4K HDMI 7 port USB-
3.5 mm Audio	•	What's in the box	Hub
Other audio ports			User Guide
Memory cards			
		Notes	
ower		*Full hub data, video and power functionality will require host device with USB-Cport compatible with DP Alt Mode *Dual monitor extension require HDMI with USB mode to be active via instal/lew instruction within user guide. Sin	Power Delivery PD 3.0 and USB 3.2 Gen 1/ Gen 2
	•	** Dual monitor extension require HDMI with USB mode to be active via instalview instruction within user guide. Sin installed even with both HDMI connected to compatible external monitors *** Compatible with optional 100 W USB-CPD charger with up to 85 W pass through to device or optional 150 W AC	gle monitor connection via HDMI port supporting DP Alt Mode only without InstaView of
JSB Power Delivery to host device	- when hub is connected to optional	*** Compatible with optional 100 W USB-C PD charger with up to 85 W pass through to device or optional 150 W AC *** Require ChromeOS* version R90 or later *** Require ChromeOS* version R90 or later **** Compatible with IP8d* with USB-C/Thunderbolt port. Extended mode to single external monitor via HDMI page.	
	USB-C PD 3.0 charger	******* Compatible with in-an-with USB-C/ Inunderbook port. Extended mode to single external monitor via HUMI po ******* Compatible only with InstaView driver download from http://www.siliconmotion.com/downloads/index.htm	al.
	•		
Max. PD power / PD pass through to host	100 W PD 3.0 / up to 85 W pass		
, p , p	through to host device***		
ecommended USB-C chargers			
lyper HJG100 100 W GaN charger	•		
Hyper HJG140 140 W Universal GaN charger	•		
argus APA108 100 W laptop charger			