



DECLARATION OF PERFORMANCE

No. 042DoP2019-11

1. Unique identification code of the product type:

Roof window primarily made of wood, extruded aluminium and glass

2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Skylux® roof window

Roof window for sloping roofs between 25° and 75°

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specifications, as provided by the manufacturer:

Natural daylight and ventilation of buildings through an opening roof window with an insect screen as standard.

4. Name, registered trade name or registered trade mark and contact information of the manufacturer as required under Article 11(5):

**Skylux,
Spinnerijstraat 100,
B-8530 Stasegem, Belgium
Tel. +3256200000
Fax: +3256219599
Email: info@skylux.be**

5. If applicable, name and contact information of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: lab notification 042

AVCP System 3

7. If the declaration of performance concerns a construction product for which a harmonised norm has been issued:

EN 14351-1:2006+A2:2016

8. If the declaration of performance concerns a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance


Essential characteristics*	Performances	Harmonised technical specification
Water tightness	Class 9A	EN 14351-1:2006+A2:2016
Acoustic performance	35 (-1;-3) standard 37 (-1;3) acoustic glass	
Wind load resistance	Class 3 (1/300)	
Air tightness	Class 4	
Heat resistance	1.3	
Reaction to fire	B-S1,d0	
External fire classification	NPD	
Shock resistance classification	Class 4	
Solar heat gain coefficient without screen % Solar heat gain coefficient with standard combi insect screen	51.7 standard/51.6 acoustic/51.5 4PA 0.1	
Resistance to repeated opening and closing	Class 5	
Resistance to burglary	RC2N standard glass/acoustic glass RC2/N 4PA glass	
Snow load resistance	Standard 5 mm tempered-16 mm-6.8 mm (33.2) laminated	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performances in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer by:

Tom Vandamme
 Technical Manager
 Stasegem, December 2019



*For all sizes of standard and Rustica windows in our range.