

Category > Maintain

Rejuvenating Cleaner

Multipurpose Cleaner with Sealer Reinforcement

Product Description

Ameripolish® Rejuvenating Cleaner is a concentrated multipurpose cleaner that removes daily debris from hard surfaces, as well as reinforces the sealer to extend the life of polished concrete floors. Rejuvenating Cleaner contains no harsh chemicals, and leaves no build-up on the surface. In addition to polished concrete, it is ideal for use on vinyl tile, ceramic tile, terrazzo, wood, and composite materials. It rejuvenates the floor by reapplying trace amounts of densifier and stain resistant additives while you clean with an auto-scrubber. This allows the reapplication of SR2 as far out as every 2 years.

Features

- Concentrated cleaner that removes daily debris from hard surfaces
- Contains chemical analogues to SR2 that reinforce stain protection
- Contains no harsh chemicals
- Environmentally friendly, biodegradable
- Easy to use tilt measure bottle
- Low VOC, VOC compliant
- Ideal for daily cleaning of polished concrete, terrazzo, epoxy, urethane and other hard surface flooring

Uses

Ameripolish® Rejuvenating Cleaner is ideal to be used on:

- Polished concrete floors
- Vinyl tile floors
- Ceramic tile floors
- Terrazzo floors
- Wood floors
- Polyester counters and sinks
- Composite materials

Dilution & Coverage

Ameripolish® Rejuvenating Cleaner should be diluted 8oz cleaner per 30 gallons of water (auto-scrubber), 4oz cleaner per 15 gallons of water (auto-scrubber) and 1oz cleaner per 5 gallons of water (mop bucket, other).

Product Specification

| | |
|---------------------|---------------------------|
| Application: | Rag, mop or auto-scrubber |
| Appearance: | Light blue |
| VOC: | Compliant (1g/l) |
| Shelf life: | 1 year |
| Solvent: | Water based |

Packaging Specification

| Product # | Shipping Wt. | Container |
|-----------|--------------|---------------------------------------|
| RJCON-10 | 50 lbs. | 32oz Tilt Measure Bottle - 10 pack |



Category > Maintain

Rejuvenating Cleaner

Multipurpose Cleaner with Sealer Reinforcement

Application

Apply Rejuvenating Cleaner with an auto-scrubber or mop diluting the cleaner with the appropriate ratios depending how the size of the tank size of the auto-scrubber. The auto-scrubber should be fitted with a non-aggressive cleaning brush or pad. Do not perform regular maintenance with aggressive pads such as diamond-impregnated pads or other abrasives. Use of aggressive pads will wear away stain protection and, in time, wear away color from the concrete surface. Clean the auto-scrubber according to manufacturer's directions. After cleaning, allow drying before resumption of traffic. Between cleanings, remove dust and debris with a microfiber pad or dry mop. Check wear of floor on a regular basis to determine if Stain Protector needs to be re-applied. Simply mix concentrated cleaner with water. Surfaces can be cleaned using a rag, mop or auto scrubber.

Cleanup

Ameripolish[®] Rejuvenating Cleaner washes up quickly with water.

Storage

- Store upright in safe dry place at 40-105F° (4 -41C°)
- Keep product from freezing
- Keep out of reach of children
- Seal container after use
- Do not mix with other chemicals

VOC Compliance

In addition, Rejuvenating Cleaner offers VOC compliance with low VOC at 1g/L and is also compliant with national, state and district regulations:

US Environmental Protection Agency
California Air Resources Board SCM Districts*
South Coast Air Quality Management District*
Maricopa County, AZ
Northeast Ozone Transport Commission*

*Before application, verify product conformance with local

and state codes.

Safety Information

Ingestion: DO NOT induce vomiting. Drink large quantities of water or milk. Seek medical attention immediately.

Eye Contact: Remove contact lenses. Immediately flush eyes for 15 minutes in clear running water; hold eyelids open. Seek medical attention if irritation persists after flushing.

Skin Contact: Wash affected area with soap and water. If irritation persists, seek medical attention. Inhalation: remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if adverse effect continues after removal to fresh air.

Warning

Before using or handling this material, read the Material Safety Data Sheet and Warranty. EYE, SKIN AND GASTROINTESTINAL TRACT AND RESPIRATORY TRACT IRRITANT. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists generated by this product. Use appropriate eye protection, and chemical-resistant gloves. Material is not flammable, but if exposed to fire material may produce irritating vapors and toxic gases (e.g., carbon dioxides and peroxides). KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

Warranty

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer. Sole remedy shall be replacement of product proven defective.