

The dream of electric technology

PERSONAL MOBILITY User Manual



Company Introduction

Minimotors Co.LTD., is a company who manufactures and distributes personal mobility with a prpfessional production system since 1999.

Minimotors Co.LTD., has been making the electric mobility brand < DUALTRON > to meet the world's people with the aim of making more innovative, more sensuous, and more convenient personal mobility since 1999 and making products that are loved by people in the world. Minimotors Co.LTD., is doing its best to become the world's best electric mobility company.



Brand Introduction

"DUALTRON" brand is a worldwide known electric scooter brand name that Minimotors Co.LTD., designed.

"DUALTRON" is a breakthrough product that combines the world's first dual drive system and the new rubber suspension technology (patent pending). It's a proud Korean luxury brand that has won the world's electric scooter market exporting to more than 30 countries.





Do not use the product until you understand its functions. Do not rent the product to anyone who can't operate the product.

*For the first time, the user should use it with a slow speed for safety.

Dualtron Eagle user manual contents

01. Safety guidelines and restrictions	04
02. Product structure	06
03. Name of each part ·····	07
04. Product components	8
05. How to use the product	09
06. How to use the instrument panel	12
07. LED BAR funtions	15
08. How to use the charger correctly	16
09. Safety precautions for Lithium-ion battery	17
10. Safety guidelines before driving	18
11. Maintenance	19
12. Important checklist·····	20
13. Product specifications	22

Before Reading Manual

This manual contains important information to help you to use your product more safely. For safe use, it is marked as 'Danger', 'Caution'and 'Warning' depending on the degree of danger and the meaning is as below.



Danger: Indicates a hazardous situation that could be a result of serious injury.



Warning: Indicates a potentially hazardous situation that could be a result in light injury.



Caution: Indicates a potentially hazardous situation that could be a result in serious injury.



✓ Please read this manual carefully

before using this product

1) Safety guidelines and restrictions

* Even if the it is within the warranty period, you may be liable for any accident caused by any of the following causes.



1. Be careful of water!

This product and components are not waterproof. Don't let the water get into the product and components.

- *Never use it, if the road is wet due to the rain, snow, hailstone.
- *If you wash or spread water to electric devices, it can result in malfunction or fire.



2. Beware of folding and spinning parts!

If parts of the body, as a finger or hair, get caught in the spinning or folding parts of the product, this may lead to severe injuries. Please be careful.



3. No acrobatics

Stunts and jumps such as jumping and dropping are prohibited as they can cause a great impact on the product and can cause of malfunction and accidents.



4. No companion boarding

This product is intended for one adult only, so children, infants, or two people are prohibited from boarding.



5. Don't tune by yourself

Do not open or tune the electric parts (battery, controller or motor system).



6. Comply with the related laws

Unlicensed, driving after drinking, loading cargo on the scooter is prohibited. [More than bike or bicycle license is required]

Please comply with the Road Traffic Act and related laws and regulations

according to the place of use.



7. Beginners and seniors are encouraged to use at low speed

Beginners who are not accustomed to use the product, seniors and others should avoid high speed mode driving and recommend low speed driving. In addition, please use after practice how to ride safely in a wide place.



8. Do not sudden brake with front brake

If there is a risk of overturning, sudden deceleration should be done safely. Do not apply any unusual behaviors or artificial forces, such as stopping with your feet.



9. Do not accelerate downhill

Slow down at downhill. When reducing the speed, to prevent brake overheat, use the brakes properly to reduce the heat on the disk with proper brake use.



10. Do not drive on steep slopes

Acceptable gradeability is different for each product. Excessive hill roads exceeding the specification may cause damage to the product(parts) due to temperature cut, overcurrent or low voltage cut, which may cause the product to malfunction.



11. Safety warning when lifting the product

If the product is lifted by holding only the handle, there is a possibility that the product may be damaged due to deformation of the folding part due to load or movement of the product. When lifting the product, be sure to hold the product's body (footrest) with one hand and hold the handle with the other hand so that you do not get hurt in your back or knees.




12. Be sure to wear safety equipment

For the safety of passengers, be sure to wear a full face helmet and the other protective gear(knee, elbow, hand, upper body) and do not wear shoes such as slippers, high hills that interfere with driving.


2) Precaution before driving

- 1. Night driving should be avoided in any case, be sure to wear helmets and other guards (knees, elbows, hands, upper body, etc.) and drive safely.
- 2. Select the mode that suits you and drive. In order to cope with the sudden situation, exercise to slow down to hold the brake at all times.
- 3. When turning left / right, slow down to avoid danger of overturning or slipping., And then slowly turn safely.
- 4. To go to backward, it is safe if you getting off from the product after stopping before moving.
- 5. It is prohibited to use in a slippery place, a crowded place, a steep slope, roads with a risk of accident, uneven road.
- 6. When crossing a pedestrian crossing, get off from the product for pedestrian safety.
- 7. Do not drive in a threat any other means of transport, such as animals, pedestrians, bicycles, motorcycles, cars, etc.
- 8. If you pass the speed bumps and obstacles, be sure to slow down.
- 9. When decelerating or braking, do not stop with using foot, but stop with using brake appropriately.
- Be careful that there is a risk of burns due to heat from motor and brake (especially disk rotor) after driving.
- 11. It is prohibited to drive with all the way by holding the handle with one hand.
- 12. Do not ride or drive when the kick stand is down.



Product structure

Product size



^{*} Errors may occur depending on the measurement method.






Body frame



Product components



Checking the components inside of the box

Top: Default battery charger(2A), Default tool, User manual, Remote control Bottom: Body(Lithum battery included)

Ejecting the productnumber.



Do not hold the handlebar only when lifting the product from the box.

Please be careful that the fixing slide of the folding part may be damaged, and a safety accident such as a part of the body may be caught.

Therefore, when lifting the product, it is necessary to raise the handle bar first, and then slowly lift the body (footrest) of the product with both hands and do not damage the folding part

Make a note of the serial number.



The serial number can be used to check information such as date of purchase, warranty period, etc., and product information can be checked even if the product is lost or stolen.

(May vary depending on branch office situation)

-Assembling of the instrumentpanel, brake



-Locate the instrument panel and tighten the fixing bolts.



-Adjust the position of the brake and tighten the fixing bolts with a 5mm hexagon wrench.

How to use the product

DUALTRON EAGLE

1) Productun folding



1. Raise the handle post(Steering tube)

Release the QR lever, raise the locking slide upwards, raise the steering tube. then lower the locking slide downward.



2. Raising handle post(Steering tube)

When unfolding the steering tube, raise the handlebar while pushing the deck with foot, and then lower the loking slide down completely and tighten the right finishing screws.



3. Fixing the folding part

When the QR lever is locked inward as shown in the picture, the handle unfolding is completed. If the folding lever is not completely locked, a safety accident while driving can be occurred. Before and after running, always check if there is a play in the folding part, and a folding part or handle part, the bolt&nuts of all the fixing parts of the product are properly tightened and the fastened parts are not loosened.

How to use a product

2) How to start



Step1. Turning on the main switch

When turning on the product, you can start driving by turning on the main power switch first (when using the built-in battery) and turning on the power of the LCD panel. When driving is finished, turn off the LCD panel and turn off the main power.

* The power of the instrument panel will turn off automatically after a few minutes of inactivity. At this time, the LED lamp is also turned off, so turn it off with the LED lamp button when you turn it on again, and turn off the main power switch after use.



Step3. Stance for driving

After tilting the kickstand, find a stable position on the footrest and then hold the handle grip comfortably. Be careful not to raise your foot on the rear fender.



Step2. Turning on the instrument panel

Press the POWER button on the instrument panel for 2 seconds to turn on the instrument panel. You can set the start mode, cruise mode, electronic brake, and ABS function.



Checklist before turning on the product

Before turning on the product, turn on the power with the LED lamp turned off. Index throttle



Step4. Acceleration and deceleration

Acceleration can be performed by using the throttle of the instrument panel while driving, and the deceleration or stop can be performed by holding the brakes on the handle.



Before driving, be sure to check the folding part, the handle part, the part where the main fixing part of the product is fastened well. And check the position of the fixing slide, the QR lever locking status and the folding part fixing status.

Throttle malfunction caution

Regardless of whether the throttle is operated or not, the motor sensor may continue to operate, causing malfunctions such as sudden acceleration. In this case, holding the brake lever to cancel the operation. This phenomenon may be caused by corrosion of the throttling, immersion of the throttle, disconnection of the magnet, broken off levers, and breakage of the spring. Do not bounce the throttle lever strongly.

3) How to stop

Step1

Rear brake use

Be sure to use the rear brake first for decelerating when stopping while driving. For safe stop, it is necessary to practice slow down after deceleration with rear brake

Step2

Front brake use

Always use the front and rear brake levers together to stop smoothly and safely after decelerating with the rear hrake





Driving mode Motor system Click Click again (Low speed) (High speed)

Rear wheel (Front&rear two wheel driving)

Step4

Deceleration and braking using electric brake

Set the use and strength of the electronic brake among the detailed functions of the instrument panel before driving. When the brake lever works, the electronic brake works together to increase the braking force.

Check for safe braking

• For safe braking, check whether the brake lever and disc caliper connection (wire damage, external breakage, etc.) are damaged before and after driving, and check brake wear and looseness of brake inner core(Inner wire). In the case of hydraulic brakes, it is also necessary to check the oil leakage or deficiency and always check that the braking force is sufficient. • Due to various factors such as road surface condition and speed, it may not be possible to stop when brake is operated as expected. The electronic brake and ABS functions are auxiliary functions to further increase the braking force and used. The user should understand the function and expect the operation timing when use this function.

4) Product folding



1. Releasing fixing folding part

Unfold the QR lever outwards and pull the locking slide up, and then lay the steering tube in the direction of the arrow.



2. Folding handle post

When folding the steering tube, hold the post and lower it toward the deck, Raise the locking slide up and tighten the right finishing screws.




3. Fixing folding part

Fold the QR lever inward as shown in the picture and fix it to complete the product folding.

How to use the instrument panel





1) Speed step setting Can adjust with button.

While the instrument panel is on, press
to set the speed step. The setting is completed when the selected speed step value is selected.

* Blinks 3 times per 10 seconds when the remaining battery power is 10%. It blinks continuously when the remaining battery power is 0%.

2) Functions and settings for each main screen mode Can adjust with button.




Mode	Discription		
TRIP	Current mileage(Press and hold mode button to reset to '0')		
OD0	Accumulated mileage		
CHA	Not use		
VOL	Current voltage		
TIME	Drived time		


3) Instrument panel detailed function

You can change the setting mode by turning on the power of the dashboard and pressing for $2\sim3$ seconds.

* If you change the default setting values P0 (10), P1 (60), P2 (10), P3 (0), correct information will not be displayed.



Setting value



- 1. Displaying speed unit selection P4: 0 (Km/h), 1 (mp/h)
- 2.Start method selection P5: 0(Acceleration start), 1 (Kick start)
- 3. Cruise mode selection P6: 0(Off), 1(On)
- 4. Slow start P7: 0 (Slow start off: Power start) ~ 5 (Slow start)
- 5. Battery save mode P9: 1 (MAX SAVE), 2 (MID SAVE), 3 (NO SAVE)
- 6. Electronic brake setting mode PA: 0 (Electronic brake off) ~ 5 (Strongest)
- 7. LCD brightness adjustment Pb: 0 (Backlight off) ~ 5 (Highest illumination)
- 8. Auto off time setting PC: 1 ~ 30 minutes
- 9. ABS setting Pd: 0 (OFF), 1 (ON)

4) Features of cruise mode (automatic driving)

The cruise control function allows you to maintain the driving speed automatically. Take advantage of cruise features

The advantage of being able to reduce fatigue when traveling long distances and to increase mileage of driving due to constant speed driving.

(1) The start of the cruise function

Select the Cruise function section of the dashboard as 'Settings' and set the throttle to the same Acceleration. The cruise function will start.



(2) End of cruise function

When you hold and release the brake while cruise mode is in effect, the cruise mode is automatically released

Precautions when using the cruise function



- * In case of cruise function, <u>please ride in a position where brake can be used immediately</u> so that cruise function is canceled and braking is possible in preparation for safety situation while driving.
- * When switching from dual drive mode to single mode in cruise mode, it is not possible to cancel cruise mode by using throttle and it is only possible to release by braking.

How to use the instrument panel



5) Setting of Electronic brake





Precautions when using electronic brake immediately after full battery charge

The electronic brakes do not operate when the battery is fully charged, so be sure to check and operate this device. When the battery runs out, the electronic brake will operate normally

6) ABS function setting guide

All electric motorcycles are subject to sudden braking, causing the wheels to stop spinning. As a result, the slip of tire causes the driver to fall down, which can cause accidents. This product is equipped with ABS brake function to hold the tire lock, enabling more secure braking.



ABS OFF



(1) ABS function ON

Set the ABS function part Pd of the dashboard to 1.

(2) ABS function OFF

Set the ABS function part Pd of the dashboard to 0.

* Pd - When the ABS function is ON, the PA electronic brake function is canceled

* ABS brake is an abbreviation of Anti-Lock Brake System. It uses the principle that maximum static friction force is larger than kinetic friction, so that braking distance (distance from breaking to stopping) is shorter than that of normal brake. It has the advantage that the vehicle does not slip well when wheel is rotating andit is a brake assist system that can stop more safely without wheel lock and slip.



* Precautions when using the ABS function

ABS has the advantage of being able to stop at the shortest braking distance that can be obtained from the tires and road conditions. However, due to the principle of repeatedly holding and releasing the brake several times in a second, a lot of vibration occurs in the motor and the body. Repetitive vibration caused by this may cause frequent loosening of the motor, rim, fixing part and body fixing bolt.



7) Self-diagnosis through dashboard



Fault type	Diagnosis	Solution	
0	System error	* If the error information appears, immediately stop using the product and take the scooter to the service center before use. Excessive use can result in damage to the product and safety accidents.	
4	Motor error		
6	Accelerator error		
6	Controller error		
089	None		

^{*} The number 1 is displayed when the cruise function is executed at a constant speed.

1) LED function guide


When the LED is turned on, the main power is turned on and the LED bar is lit when the throttle power is turned on, Make sure that the LED lamp button on the right side of the deck is turned on.



LED Lamp button

2) Remote control functions and settings

The LED remote control is infrared. Please use the remote control on the right side cover.



^{*} The number (a) is displayed when the brake lever is operated. (When the indicator lights, the accelerator does not operate.)

How to use a charger correctly

1) Basic charging method

1. Open the chargingport cap and connect it to the connector of the charger and connect it to the household outlet.



- 2. Charging status indicator (Red) Charging (Green) Charging complete
- 3. Be sure to close the chargingport cap when driving or storing except when charging.

Auxiliary batten

4. When connecting the connector to the charging port, metallic sparks due to voltage difference may be splashed, but this is normal

2) Basic charging method

* Failure of the charger and abnormal conditions can cause

electric shock and fire. Learn the correct usage and prevent safety accidents in advance.

1.Manufacturers and sellers are not responsible for any problems arising from any disassembly, modification, or mixing with other chargers.



2. The charger is forbidden to be used in places subject to high humidity, heat, flammable materials, confined spaces, or where there is no ventilation such as in a car.



3. The charger is not waterproof. It is thoroughly controlled to prevent (moisture from entering the charger.



4. Children and pets should not be allowed to approach the charger when they come into contact with them, as they may cause an electric shock.



5. If the charger lamp does not light, charger fall, strong external shock, long time charge, or cable cover damage, discontinue use immediately and contact the service center.



6. Unplug the charger when you are away from the home for long periods of time.



- 7. Use only genuine charger.
- 8.Do not insert conductors into the charging port.



- 9. Do not touch the plug for about 10 seconds after unplugging the charger. There is a risk of electric shock from instantaneous discharge.
- 10. Do not remove the terminal during charging. Charge the internal circuit of the charger and cause malfunction.
- 11. Do not operate the product during charging.
- 12. Charging terminals should be firmly contacted during charging and should not be used if terminals are corroded or damaged.
- 13. When disconnecting the charger from the product, it is safe to hold the terminal without holding the wire.

Safety precautions for Lithium battery

DUALTRON EAGLE

- **1. Care** Lithium batteries should be protected from direct exposure to children and pets.
- 2. Performance ① Lithium battery is affected by external temperature. In winter, when the temperature is low, the performance of the battery is temporarily deteriorated and the mileage and power output is reduced.
 - 2 Lithium battery has a characteristic that discharge performance is reduced by more than 15% when charging / discharging 300 times or more. If usage time is shortened due to long usage, it should be replaced with a genuine one through the nearest point.



- **3. Charging** (1) Lithium battery should be used only with genuine battery and charger supplied from the manufacturer. Any problems caused by use of battery made by the manufacturer, mixed use, or using the charger are not covered by the manufacturer.
 - ② Charging the lithium battery with a non-genuine charger may cause malfunction or fire.
 - 3 The lithium battery should be charged in a well-ventilated, dry place and around the charger in a place where there is no inflammable material.
 - ♠ Lithium battery should be charged at 0 ~ 45 °C and discharged within -10 ~ 60 °C. Charging or discharging at a temperature outside this range may cause malfunction, fire or explosion.
 - ⑤ In case of moving from cold outside to warm indoor, please charge it after 1 ~ 2 hours. This is to prevent condensation from occurring inside the product due to temperature difference.
- **4. Storage** ① Lithium batteries should be kept away from snow, rain and direct sunlight. Do not store or charge them in a trunk or hot room. Select a dry place and store at room temperature (10 ~ 20 °C).
 - 2 When storing for more than 3 months, charge the remaining battery level to 70 ~ 80% (do not store full charge).
- 5. Trouble symptom, safety (1) Lithium battery should be discontinued immediately if it is damaged or leakage of battery, sour odor, appearance deformation, etc., and contact the place of purchase to get technical support and service.
 - ② If overheat, smoke or ignition is detected in a product with lithium battery, immediately stop charging and use, move the product outdoors as soon as possible, and then use a fire extinguisher to evolve. Do not spray water or immerse the product in order to evolve, which is more dangerous.
 - 3 Lithium battery pack has very high energy density, so if you charge the battery for a long time in case of short-circuit, leakage, bad battery, etc., there is a possibility of ignition. Therefore, you should avoid charging for a long time without a person, and charging must be done while the person is aware that the risk of unexpected fire can be avoided.
- **6. Misuse** If the lithium battery is short-circuited or the polarity is changed, or if the battery is impacted, malfunction or fire may result. If you think that the battery has been impacted, you should stop charging and using it and visit the nearest point for inspection.
- 7. Water inflow It should be controlled to prevent water inflow into the lithium battery. There is a risk of fire or electric shock if the charger is connected while moisture is present.
- 8. Caution Disconnect the battery from the main unit and prohibit recharging, reinstalling, or using other applications.
- **9. Disposal** DisposalWhen disposing of the lithium battery, the battery should be separated from the product at the point of purchase or near the point so that the charge and discharge terminals are not short-circuited. Dispose of it as industrial waste when disposing of it.



Battery disassembly prohibited

Danger Battery disassembly, modification and repair are not covered under warranty.

Safety guidelines before driving

1) Required checking before use

1 Check throttle and handle

- Operate the accelerator throttle lever about 2 ~ 3 times to check whether it returns to the home position.
- Be careful that excessive throttle leaning and manipulation of the throttle can cause malfunction due to internal parts damage.
- Check the fastening condition and clearance of the QR lever on the handle.



2. Check brake and cable

- The brake braking force is sufficient to check the operating condition. If the braking force is significantly lowered, use it immediately after inspection and action.
- Check that the brake pad is not worn, that the cable is not loose, that the cable is not damaged, or that there is no leakage in the case of hydraulic brakes.
- If there is an unusual feeling or noise during operation, check for breakage, wear and deformation of the inner wire of the brake cable.
- Check that the bolts and nuts of the brake fixing parts are not loose, and that the disc is not deformed or damaged.



3. Check tire pressure and uniaxial condition

- Check the front and rear tires for wear and punctures and check the proper air pressure (45 to 50 psi) for the tire. When the shortage of air is shortened, the possibility of puncture increases, so check always.
- It is necessary to judge the replacement time by observing the appearance of the tire such as tire damage, uneven wear.



4. Tightening check such as folding part and handle part

• Make sure that the bolts and nuts of all parts of the product are tight and free from loosening. Check the fastening condition and clearance of the folding and fixing parts of the handle (QR lever, fixed slide, hinge center bolt, headset nut, swing arm. etc.).





* If there is a folding clearance.

If there is a folding clearance, it can be adjusted with a tongue bolt. However, if Danger you pull it too hard, it will become stiff without a gap, but it may sound 'crackling'. In this case, if you adjust the tune bolt properly, the noise disappears and the clearance is also adjusted.



* In this case, stop driving immediately.

If you encounter any of the following situations while driving, stop driving immediately and contact your nearest branch or service center for proper measures. If you provide pictures and videos to get accurate diagnosis, professional counseling is available...

- Unusual heating of the motor
- Brake braking status error
- Error messages on the instrument cluster
- When the throttle is returned to its original position
- When the throttle is returned to its original position
- abnormal noise is generated
- Product smoke, ignition, sour odor
- When rain or wet with water or in a similar situation
- When other driving is judged to be unreasonable

2) Maintenance and self-maintenance

Electric products can be damaged by various factors. The life span of each part varies depending on driving habits and driving environment. Parts that exceed the service life may cause accidents. Let's manage various parts and prevent safety accidents in advance.



2YEARS / 7.000


1YEAR / 5.000

2YEARS/ 10.000

If the exterior is

1. Check the replacement timing of consumable parts

- * The rubber inside the rubber suspension is cured as the consumable parts are used, and the performance of the suspension is slightly reduced because of the reduced elasticity.
 - 1) The components and suspension parts of the car swing arm, tires, tubes, wheels, bearings, headset bearings, discs, brake pads, cables and folding parts, various brackets and other consumable parts requiring periodic inspection and always check.



2. External damage inspection by driving environment



- ① Replace parts that may be damaged by external driving environment, such as deformation of parts, cracks due to compression, and signs of exceeding fine gold or life expectancy.
- (2) If the product is exposed to strong sunlight for a long time, discoloration may occur.
- ③ In case of heavy driving such as normal jumps, slight impacts such as turning, collision, etc., when driving frequently or for a long time in a poor road condition or driving for thousands of kilometers or more, fatique breakdown phenomena Please check and replace the parts replacement schedule for each product for safety.
- 4 Fatigue breakdown and maintenance parts may differ from the example conditions depending on the driving environment and the operating conditions. Also check parts other than the replacement cycle (maintenance parts) at all times to check for any signs of abnormality.



Important notice

Important notice



* Metal vibration may occur due to motor vibration, vibration of the brake disc and pad during the load section that accelerates during driving. (About $15 \sim 30$ Km, different for each product)

This is a phenomenon in which all revolutions (fans, automobiles, ships, etc.) are vibrating at a specific rotational frequency (rpm) rather than the product. However, if the continuous noise or metal noise is large, there is a possibility that the disk is bent and deformed.

- * Please note that after running, there is a risk of burns due to the heat on the motor and brake (especially disk rotor) side.
- * Be careful that the bolts of the motor, rim and motor shaft due to the ABS function may be loosened.

3) Maintenance by self-maintenance

1. Brake adjustment method

As you continue to use the brakes, the brake pads become worn out and the gap between the pads and the brake disc becomes wider. If the braking force drops, use a 5mm hexagon wrench to loosen the brake arm wire bolt, then lift the brake arm upwards to adjust the braking force.



2. Causes and countermeasures of disc brake noise

The disc braking method uses a disc brake method with many electric kickboards because braking power is good. However, if you get a sharp hissing sound when you hold the disc brake, dust or sand particles on the ground will spill out on the surface of the disc, causing foreign substances to be on the brake pads or disc surface, or bending due to heat or external impact. At this time, clean the inner surface of the disc by turning the wheels with a clean, dry cloth, or straightening the bent discs.





If the above measures are not taken, please visit the nearest branch and take a safety check. There may be another problem.



3. Variable rear rubber suspension system (patent pending) adjustment

Designed by MINI Motors, 5-step adjustable rubber suspension system allows you to adjust the suspension strength with rubber cartridge replacement (5 steps).

- 1. Remove the rear fender with a 3mm hex wrench, loosen the 12mm(motor sider), 12mm(swing arm side) nut, and then loosen the nut to remove the suspension arm.
- 2. Adjust the rubber cartridge replacement, and desired suspension strength.

■ Rubber Replacement (5th Stage): Replace Cartridge (Adjust height by weight)

Loosen both nuts with a wrench, loosen 3mm bolts and remove. Replace the cartridge when it is missing.

(It can be changed depending on weight and taste)






3. Align both suspension arms to the desired angle and reassemble using Loctite (screw lock).

Product Specification

Product Name	EAGLE	EAGLE PRO	Note
Motor	MA	AX 3300W BLDC DUAL	HUB MOTOR
Battery type	Li-Ion battery pack		
Battery capacity	60 V 18.2Ah	60 V 22.4Ah	
Charging time (1.75A)	10.4hr+	12.8hr+	Standard charger(1.75A)
Charging time (3.5A)	5.2hr+	6.4hr+	2EA of standard charger(1.75A)
Charging time (6.5A)	2.8hr+	3.4hr+	Quick charger(6.5A, Optional)
Charging time (8.25A)	2.2hr+	2.7hr+	Quick charger(6.5A)+Standard charger(1.75A)
Max mileage	60km	80km	75±5kg load, 25km/h flat road continuous riding
Max Speed	25km/h		
Folding	Handle post two touch double folding		Patent pending
Gradeability	Around 43% (23°)		Weight, road condition, battery status temperature affect to the gradeability
Max load	120kg		
Product weight	Around 30kg		
Unfolding size	1185 x 600 x 1200mm		Length x Width x Height
Folding size	1185 x 600 x 505mm		Length x Width x Height
Dashboard	EYE throttle is applied as the default option.Bettery level, TRIP, ODO, Time Speed and mode change.Start method,Cruise system,Slow start,Speed limit Battery save Electric brake,ABS,LCD brightness control.Auto off time setting		
Light	Handlebar sides LED lights,Dual LED headlight&taillight,brake light		DC to DC converter is built in (12V 3A output)
Brake	Front and Rear Disc brake +Electric ABS.		Common use for front and rear wheel
Suspension	Front -Rubber Suspension,Rear-5 kinds of rubber cartridge replaceable design		Soft,medium soft,hard,medium hard cartridge is optional/Patent pending
Tire	10inch(10x2.5) 4PR wide tube tire		Tire width : Approx. 6.5cm Proper air pressure 45~50psi
Product material	Frame and handle: Aviavion aluminum forging alloy, 6082-T6, Ultralight Carbon Fibre, Shaft: SCM440, Covers: Polypropylene		

^{*}The specification can be changed by manufacturer without notice to improve the quality and safety for users.

^{*}The distance can be affected by loaded weight, wind direct (wind speed), road condition, slope and tire condition.



DUALTRON EAGLE Electric Scooter User Manual

Zhejiang Minimotors Bike Co., Ltd.

No.1, Baolong road, Lanjiang Street, Lanxi Economic development zone, Jinhua city, Zhejiang province, China

Tel: +86-173-6971-8326 www.dual-tron.com

