

SAFETY DATA SHEET **JL69**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

JL69

Identified uses Lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier

VeloBrands Ltd, Copplestone Mill, Copplestone, Devon, EX17 5NF sales@juicelubes.co.uk

1.4. Emergency telephone number

Emergency telephone	+44 (0) 1363 85617		
SECTION 2: Hazards identifica	SECTION 2: Hazards identification		
2.1. Classification of the subst	ance or mixture		
Classification (EC 1272/2008)			
Physical hazards	Aerosol 1 - H222, H229		
Health hazards	Eye Irrit. 2 - H319		
Environmental hazards	Not Classified		
Classification (67/548/EEC or 1999/45/EC)	Xi;R36/38. F+;R12. R66.		
Human health	Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.		
Environmental	The product is not expected to be hazardous to the environment.		
Physicochemical	Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.		
2.2. Label elements			
Pictogram			



Signal word

Danger

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H319 Causes serious eye irritation.
Precautionary statements	 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P260 Do not breathe vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P501 Dispose of contents/ container in accordance with local regulations.
Contains	Sodium sulphonate

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.		
SECTION 3: Composition/information on ingredients		
3.2. Mixtures		
Distillates (Petroleum) Hydrotreate	ed Light	30-60%
CAS number: 64742-47-8	EC number: 265-149-8	REACH registration number: 01- 2119484819-18
Classification Asp. Tox. 1 - H304	Classificatio Xn;R65. R6	on (67/548/EEC or 1999/45/EC) 66.
PETROLEUM GASES, LIQUEFIE	D; PETROLEUM GAS	30-60%
CAS number: 68476-85-7	EC number: 270-704-2	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280		on (67/548/EEC or 1999/45/EC) rc. Cat. 1;R45 Muta. Cat. 2;R46
Sodium sulphonate		1-5%
CAS number: 68608-26-4	EC number: 271-781-5	REACH registration number: 01- 2119527859-22
Classification Eye Irrit. 2 - H319	Classificatio Xi;R36.	on (67/548/EEC or 1999/45/EC)
The Full Text for all R-Phrases and	Hazard Statements are Displayed in Se	ection 16.
SECTION 4: First aid measures		

4.1. Description of first aid measures

General information Move affected person to fresh air at once.

InhalationIf spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and
keep warm and at rest in a position comfortable for breathing. If breathing stops, provide
artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion	Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.	
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.	
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.	
4.2. Most important symptoms	and effects, both acute and delayed	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.	
4.3. Indication of any immediat	e medical attention and special treatment needed	
Notes for the doctor	Treat symptomatically.	
SECTION 5: Firefighting meas	ures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build- up.	
5.3. Advice for firefighters		
Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.	
SECTION 6: Accidental releas	e measures	
6.1. Personal precautions, prot	ective equipment and emergency procedures	
Personal precautions	Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.	
6.2. Environmental precautions	<u>8</u>	
Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.	
6.3. Methods and material for o	containment and cleaning up	
Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.	
6.4. Reference to other section	<u>8</u>	
Reference to other sections	For personal protection, see Section 8. For waste disposal, see Section 13.	
SECTION 7: Handling and stor	age	
7.1. Precautions for safe hand	ing	

Usage precautions	Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.
7.2. Conditions for safe stora	age, including any incompatibilities
Storage precautions	Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
7.3. Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
SECTION 8: Exposure Cont	rols/personal protection
8.1. Control parameters Occupational exposure limit Distillates (Petroleum) Hydro	—
	hour TWA): WEL 800 mg/m ³
PETROLEUM GASES, LIQU	JEFIED; PETROLEUM GAS
	-hour TWA): WEL 1000 ppm 1750 mg/m³ 5-minute): WEL 1250 ppm 2180 mg/m³ e Limit
Ingredient comments	WEL = Workplace Exposure Limits
8.2. Exposure controls	
Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.
Personal protection	When using do not smoke.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.
Hand protection	Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Hygiene measures	Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.
SECTION 9: Physical and C	hemical Properties
9.1. Information on basic ph	ysical and chemical properties
Appearance	Aerosol.
Colour	Amher

Colour	Amber.
Odour	Characteristic.
Initial boiling point and range	-40 to -2°C @ 1013 hPa
Flash point	<-40°C

Revision: 2

JL69

Upper/lower flammability or explosive limits	Lower : 1.8% - Upper 9.5%	
Vapour pressure	ca. 590 to 1760 kPa @ 45°C	
Vapour density	ca. 1.5 at 15°C	
Partition coefficient	log Pow: ca. 2.3 to 2.8	
Auto-ignition temperature	410 - 580°C	
Comments	Information given is applicable to the major ingredient.	
9.2. Other information		
Other information	Not available.	
Volatile organic compound	This product contains a maximum VOC content of 600 g/l.	
SECTION 10: Stability and rea	activity	
10.1. Reactivity		
Reactivity	Stable at normal ambient temperatures and when used as recommended.	
10.2. Chemical stability		
Stability	Heat, sparks, flames.	
10.3. Possibility of hazardous	reactions	
Possibility of hazardous reactions	Does not decompose when used and stored as recommended.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.	
10.5. Incompatible materials		
Materials to avoid	Keep away from oxidising materials, heat and flames.	
10.6. Hazardous decompositio	on products	
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.	
SECTION 11: Toxicological information		
11.1. Information on toxicolog	ical effects	
General information	Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.	
Inhalation	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.	
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause	

contact Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic healthIn high concentrations, vapours and aerosol mists have a narcotic effect and may causehazardsheadache, fatigue, dizziness and nausea. Arrhythmia (deviation from normal heart beat).

Revision: 2

JL69

Route of entry	Inhalation	
Target organs	Central nervous system Respiratory system, lungs	
Medical symptoms	Skin irritation. Arrhythmia (deviation from normal heart beat). Vapours may cause drowsiness and dizziness.	
SECTION 12: Ecological Info	rmation	
Ecotoxicity	No negative effects on the aquatic environment are known. The product is not expected to be toxic to aquatic organisms.	
12.1. Toxicity		
Toxicity	Not available.	
12.2. Persistence and degrad	lability	
Persistence and degradability	v Not available.	
12.3. Bioaccumulative potenti		
Bioaccumulative potential	Not available.	
Partition coefficient	log Pow: ca. 2.3 to 2.8	
12.4. Mobility in soil		
Mobility	Not known.	
12.5. Results of PBT and vPv	Bassessment	
Results of PBT and vPvB assessment	Not available.	
12.6. Other adverse effects		
Other adverse effects	Not available.	
SECTION 13: Disposal consid	derations	
13.1. Waste treatment method	ds	
General information	Do not puncture or incinerate, even when empty.	
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.	
SECTION 14: Transport information		
General	This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.	
14.1. UN number		
UN No. (ADR/RID)	1950	
UN No. (IMDG)	1950	
UN No. (ICAO)	1950	
14.2. UN proper shipping nan	ne	

Proper shipping name (ADR/RID)	AEROSOLS		
Proper shipping name (IMDG)	AEROSOLS		
Proper shipping name (ICAO)	AEROSOLS		
Proper shipping name (ADN)	AEROSOLS		
14.3. Transport hazard class(es)			
ADR/RID class	2, 5F		
ADR/RID label	3		

ICAO class/division

Transport labels



IMDG class

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

2.1

2.1

14.6. Special precautions for user

EmS 2-13

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Supplemental information added.
Revision date	29/07/2015
Revision	2
SDS number	12628
Risk phrases in full	R12 Extremely flammable. R36/38 Irritating to eyes and skin. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking.
Hazard statements in full	 H220 Extremely flammable gas. H222 Extremely flammable aerosol. H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.