



MATERIAL: 6061 CASE ANODIZED LED CASE STAINLESS HARDWARE COATING: BLACK ANODIZE	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE MM.		<h1>LED STACK MODULE - M16</h1>			
	DECIMALS: $\frac{X}{Y} = \frac{.5}{25}$ $\frac{X}{Y} = \frac{.125}{125}$ Angles: MACHINED $\pm .04^{\circ}$ OTHER $\pm .2^{\circ}$ CONCENTRICITY: 25mm		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NODEDESIGN LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF IS STRICTLY PROHIBITED.			
	BREAK CORNERS: 125 - 25mm FILET RADII: .50 - 1.5mm SURFACE FINISH: 125 RMS		DRAWN: MEM ENGR: MEM		DATE: 6-9-21 DATE: 6-9-21	SIZE: A MADE IN AMERICA SCALE: MM WEIGHT: 425 GRAMS SHEET 1 OF 1 3RD ANGLE PROJECTION
	NOTE: IP67		REV: A		WWW.NODEDESIGN.COM	