

**LF3640 Optically Clear Gloss
LF3640G Gloss**

Media: 1.5-mil Highly Conformable Cast PVC Film

Adhesive: Clear, Permanent Acrylic Pressure-sensitive

Liner: 1.2-mil Polyester Liner | 50# Calendered Paper



Features and Benefits:

- Built-in UV protection
- Optically clear gloss and gloss finishes
- Part of the B•free® application warranty
- Five to seven years outdoor durability

Typical Uses:

- Highly conformable for vehicle graphics, fleet, marine and textured wall graphics
- Image enhancement
- Marine graphics
- LF3648 with polyester liner used for perforated window film

Use with:

- B•free® Gruv™ - pgs 8, 12-13
- WindowVIEW® - pgs 20-21

Physical Properties	Typical Values
Peel Adhesion , lb/in. (N/25 mm)	
Stainless Steel	- 20 min. 3.0 (13.1) - 24 hr 3.7 (16.5)
Quick Tack SS , lb./in2 (N/25mm)	2.5 (11)
Dimensional Stability , (in.)	
48 hours@158°F	max 0.01
Temperature Ranges	
Application:	40° F (4°C) for best results
End Use:	-50° to 225° F (-45° to 107°C)
Shelf Life:	Two years when stored at 75°F (24°C) and 50% relative humidity or less. Note: Mactac recommends the rolls be stored on end or suspended from the core.

Stock No.	Roll Width x Length	Weight: Pounds
LF3648	54" x 150'	30
LF3642G*	30" x 150'	17
LF3648G	54" x 150'	30
LF3649G	60" x 150'	34

* 2 Roll minimum

walls floors signage vehicles

Durability

5 yr

Finish

optically CLEAR finish

Adhesive

Semi Permanent

Special Features

CURVED surface

LF3630G Matte

Media: 1.5-mil Highly Conformable Cast PVC Film

Adhesive: Clear, Permanent Acrylic Pressure-sensitive

Liner: 50# Release Liner



Features and Benefits:

- Built-in UV protection
- Part of the B•free application warranty

Typical Uses:

- Highly conformable for vehicle graphics, fleet, marine and rough wall graphics
- Flat, curved, corrugated and riveted surfaces

Use with:

- B•free Gruv - pgs 8, 12-13
- RoughRAP® RR100 - pg 19

Physical Properties	Typical Values
Peel Adhesion , lb/in. (N/25 mm)	
Stainless Steel	- 20 min. 2.0 (8.7) - 24 hr 3.1 (13.2)
Quick Tack SS , lb./in2 (N/25mm)	2.5 (11)
Dimensional Stability , (in.)	
48 hours@158°F	max 0.01
Temperature Ranges	
Application:	58° F (10°C) for best results
End Use:	-50° to 225° F (-45° to 107°C)
Shelf Life:	Two years when stored at 75°F (24°C) and 50% relative humidity or less. Note: Mactac recommends the rolls be stored on end or suspended from the core.

Stock No.	Roll Width x Length	Weight: Pounds
LF3638G	54" x 150'	30
LF3639G	60" x 150'	34

walls floors signage vehicles

Durability

5 yr

Finish

MATTE finish

Adhesive

Semi Permanent

Special Features

CURVED surface