



EZCreaser



Low- to medium-volume creasing, perforating and scoring




Top friction-feed operation

Automatic sheet set-up with a single touch

Supports perfect-bind covers

Rotary perf, optional micro-perf and score wheels available

Auto setups of all the following:



Get the features and speed you need, in an easy-to-use, affordable machine.



CAM Actuated Compression Creasing



Rotary Perf and Score



Micro Lateral Adjustment

The COUNT™ EZCreaser gives you the robust features you need at an economical price, for lower to medium volume creasing, perforating and scoring. You get the speed and reliability of a top-feed automatic friction paper feeder, with smooth, consistent operation. You get a machine that's simple to set up, and easy for anyone to use with the popular COUNT touch-screen operation, and one-touch automatic set-ups built in. You get even higher speeds when operating in perf mode, with 5 interchangeable perf (including micro-perf) and score assembly options available.



EZCreaser

An easy-to-use, affordable solution for low- to medium-volume creasing, perforating and scoring.



Features

- Offers a reliable top-load friction paper feed.
- CAM actuated compression creasing.
- Automated distance recognition allows auto setups for your most common creases and corresponding folds, including perfect bind.
- Comes standard with rotary perf wheel assembly.
- Optional micro-perf and score wheel assemblies are available.
- Includes micro-laterally adjustable feed rails and a sheet counter for batch and total counting.
- An ideal companion to the COUNT KF-200 for inline folding.
- Two-sided die creasing rod accommodates for heavier stock- simply remove and flip over to change from narrow to wide crease.
- User-friendly touch screen for easy set up and control of the machine.

Automatic Set-Up for Many Common Folds

Half
Tri-Fold
Z-Fold
Letter Fold
Roll Fold
Gate Fold
Double Gate Fold
Double Parallel Fold
Perfect Bind - No Hinge
Perfect Bind - Single Hinge
Perfect Bind - Double Hinge

Specifications

Model:	EZCreaser
Model No.:	EZCREASER
Paper Feed:	Friction
Weight:	144 lbs (66 kg)
Max Compression Crease: (sheets per hour)	4,500
Max Rotary Perf/Score Speed: (sheets per hour)	12,000
Paper Weight Range: (gsm)	60 - 350
Dimensions:	47.0 L x 29.0 W x 22.0 H in (119.4 x 73.7 x 55.9 cm)
Max Sheet Size:	24.0 L x 17.0 W in (61.0 x 43.2 cm)
Min Sheet Size:	4.5 L x 4.5 W in (11.4 x 11.4 cm)
Electrical:	115 V, 60 Hz, 20 A or 230 V, 50 Hz, 20 A
Made in:	U.S.A.



Distributed by:



Image Control Systems Northwest
GRAPHIC ARTS EQUIPMENT & SUPPLIES
425-522-3347 • www.imagecontrolsystems.com