



| DAMPER INFORMATION | | | | | THCK G: | APPLICATION | |
|--------------------------|--|---------------------------------|---------------------------------|---------------------------------|--------------------------|---|--|
| TEETH: 26 | | TORQUE: 450 ft lb 610.118 Nm | | | N/A N/A | DAMPER | |
| DIA A: 13.25 [336.55] | | HOLE DIA S: 0.325 [8.25] | HOLE DIA X: 0.388 [9.86] | HOLE CEN. V: 10.875 [276.23] | THCK H: 0.800 [20.32] | | |
| DIA B: 5.880 [149.35] | | HOLE DIA T: 0.325 [8.25] | HOLE DIA Y: 0.326 [8.28] | HOLE CEN. W: 12.625 [320.68] | OAT: 0.800 [20.32] | NOTES: OEM # 1004-650-007 OEM # AS7-K2C | |
| DIA C: 1.251 [31.78] | | HOLE DIA U: 0.326 [8.28] | HOLE CEN. S: 10.375 [263.53] | HOLE CEN. X: 11.625 [295.28] | SCALE: NONE | | |
| DIA D: 1.353 [34.37] | | HOLE DIA V: 0.325 [8.25] | HOLE CEN. T: 11.375 [288.93] | HOLE CEN. Y: 10.625 [269.88] | PART NUMBER DA-107 | | |
| DIA E: N/A N/A | | HOLE DIA W: 0.388 [9.86] | HOLE CEN. U: 12.375 [314.33] | THCK F: 0.063 [1.60] | | | |