



ECM Espresso Coffee Machine Co.

3709 1st Avenue, Burnaby, BC V5C 3V6

www.ecmcanada.net (Phone) 604-291-6363 (Fax) 604-291-6302

Aurelia Wave Digit 2 Group Spec Sheet

Water Requirements

- 3/8" dedicated cold water line with shut-off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50 ppm. If water hardness exceeds 3gpg a water softener must be installed.
- Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR.

Water Filtration System

- O Sediment / Chlorine
- O RCF 124 1100 grains
- O RCF 195-4350 grains

Power Requirements

• Volts: 220 (voltage range of 208-240

Watts: 4700Amp draw: 22

Receptacle: Nema L6-30 Twist



Nema L6-30 Twist





NSF / ANSI Std.4

WARNING: Warranty void if unit is connected without a water filtration system

The average water consumption of this machine is 4 gallons per day, which represents 128 drinks at 4oz per drink.

Gallons of Water
Used per Day

Days Until Cartridge Needs to be Replaced

Water Softener/Maintenance Calculation

Cartridge Grain Capacity

Water Hardness (grains per gallon)

Gallon Capacity
of Cartridge

Counter Space Requirements

Height: 22 inches

Depth: 23 inches


• Width: 32 inches

• Weight: 195 pounds

Drain Requirements

 Open gravity drain of minimum 1.25 inch I.D., within 4 feet of the machine.

Countertop Drain Hole Location



Shipping Dimensions & Weight

Height: 27 inches

Width: 34 inches

Depth: 25 inches

Weight: 220 pounds



I, the customer, understand that these requirements must be in when the installer arrives. Failure to have the site ready will result in additional service and travel charges, and may cause further delays in installation.			
Customer Name:		Signature:	
Company Name:			
Phone:	Fax:	Email:	