


# Prontobar Spec Sheet

**Water Requirements**

- 3/8" dedicated cold water line with shut-off valve and compression fitting (Direct Connect version only).
- Water hardness cannot exceed 3gpg or 50 ppm. If water hardness exceeds 3gpg a water softener must be installed.
- Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR (Direct Connect version only - regulator not included).

**Power Requirements**

- Volts: 220
- Watts: 2400
- Amp draw: 11
- Receptacle: Nema 6-20



Nema 6-20



NSF / ANSI Std.4

**Water Filtration System**

- Sediment / Chlorine
- RCF124 - 1100 grains
- RCF195 - 4350 grains

**WARNING: Warranty void if unit is connected without a water filtration system**

The average water consumption of this machine is 1 gallons per day, which represents 32 drinks at 4oz per drink.

**Water Softener/Maintenance Calculation**


Cartridge Grain Capacity	÷	Water Hardness (grains per gallon)	=	Gallon Capacity of Cartridge	÷	Gallons of Water Used per Day	=	Days Until Cartridge Needs to be Replaced
_____	÷	_____	=	_____	÷	_____	=	_____

**Shipping Dimensions & Weight**

- Height: 41 inches
- Depth: 28 inches
- Width: 20 inches
- Weight: 130 pounds

**Counter Space Requirements**

- Height: 24 inches
- Depth: 21 inches
- Width: 13 inches
- Weight: 88 pounds



I, the customer, understand that these requirements must be in when the installer arrives. Failure to have the site ready will result in additional service and travel charges, and may cause further delays in installation.

Customer Name: \_\_\_\_\_ Signature: \_\_\_\_\_

Company Name: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_ Email: \_\_\_\_\_