

THE WOOD VENEER HUB WOOD PANELLING ADHESIVE

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

WVH Wood Panelling Adhesive is a high performance, high tack hybrid polymer adhesive specifically formulated for bonding internal wall cladding and bathroom panels.

Its advanced construction ensures superior adhesion, allowing it to stay permanently flexible to withstand extreme temperatures and moisture.

SUPER HIGH ADHESION TO ALL WVH INTERIOR WALL PANELS.

BENEFITS

- SUPERIOR HIGH PERFORMANCE ADVANCED CONSTRUCTION FORMULATION ENSURES LONG-LASTING PERFORMANCE ON A WIDE RANGE OF SUBSTRATES & SURFACES
- EXTREMELY HIGH INITIAL TACK ZERO SLUMPING ON WALL PANELLING AND INTERNAL CLADDING
- HIGH FLEXIBILITY ALLOWS THE ADHESIVE TO WITHSTAND EXTREME TEMPERATURE VARIATIONS AND MOISTURE DAMPENING

KEY INFORMATION

- Sizes available: 290ml, 600ml
- Cure time: 24 hours (full cure), 4 hours for 85% strength
- **Coverage:** 1 x 290ml tube covers lsqm application dependant
- Colour: White

PRODUCT DATA

- Chemical Base: Modified Silicone Polymer (MS Polymer)
- Application Temp.: +5°C +24°C
- Temp. Resistance: -40°C to +90 °C
- Tensile Strength: 2,80 N/mm2
- **Elongation at 100%:** 1,75 N/mm2
- Elongation at Break: >%300



THE WOOD VENEER HUB WOOD PANELLING ADHESIVE

TECHNICAL DATA SHEET

DISCLAIMER

Due to the variation in materials likely to be used in conjunction with this product, along with user techniques and operator preferences, substrate conditions, user storage conditions & other contributing factors to the adhesive performance, The Wood Veneer Hub cannot take any responsibility for the incorrect use of this product. The Wood Veneer Hub fully advise that a test must be performed by the user in advance of any application to ensure that the user is happy with the product performance. The above recommendations are made in good faith and without liability to The Wood Veneer Hub. If you have any doubts or queries regarding this product, please contact The Wood Veneer Hub via telephone, email or by writing to us.

