

## CAA-6043-XX

### Semi-Synthetic 6000 Hour Compressor Fluid

6043 synthetic blend compressor lubricant is designed for Rotary Screw, Reciprocating and Vane air compressors. This premium lubricant gives outstanding service — even in moderately severe operating conditions. With enhanced oxidative and thermal stability, 6043 is designed to provide 4,000–6000 hours of service.

#### ATTRIBUTES

- 4,000–6,000 hours of oil life at 100°C discharge temperature
- Enhanced thermal and oxidative stability
- Protects against wear, rust and corrosion
- Resists water contamination
- Non-toxic/non-hazardous

#### TYPICAL LUBRICANT PROPERTIES

<b>6043 Grades</b>	<b>32</b>	<b>46</b>	<b>68</b>	<b>100</b>
Viscosity cSt @ 40°C	31	45	69	104
Viscosity cSt @ 100°C	5.3	6.7	9.0	12.2
Flash Point °F (°C)	428 (220)	442 (228)	453 (234)	501 (261)
Demulsibility	40/40/0	40/40/0	40/40/0	40/40/0
Copper Corrosion	1a	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0