

# ATD Series In-Line Dryers



**XL MODEL**



- ▶ EXTENDS THE LIFE OF YOUR AIR-OPERATED EQUIPMENT
- ▶ PREVENTS AIR TOOLS FROM FREEZING WHEN WORKING IN A COLD ENVIRONMENT
- ▶ REDUCES AIR TOOLS MAINTENANCE COSTS
- ▶ ELIMINATE PRODUCTION DOWN TIME



**SILICA ELEMENT (XL)**




**EATD**



**ATD-FX**

## Description

Water vapor in the compressed air lines is the leading cause of paint imperfections and damages to pneumatic tools. Typical compressed air is saturated with 100% relative humidity. That means the compressed air is carrying a lot of moisture vapor when it goes into your paint gun or other air tools.



## Specifications and ordering information:

Housing	Air flow 100 psig scfm	Inlet/ Outlet NPT in	Dimensions (in)		Replacement kit	Fixing Clip	Weight (lbs)
			A	B			
ATD- 1/4	22	¼	2 ⅝	10 ⅛	EATD	ADT-FX	2.5
ATD- 1/2	44	½	3 ⅝	10 ⅛	EATD	ADT-FX	2.5
ATD- 1/2-CL	44	½	3 ⅝	10 ¾	EATD-CL	ADT-FX	4.2
ATD- 1/4-XL	25	¼	3 ⅝	14	EATD-XL	included	6