



D15 ENGINEERING DATA SHEET

Engineering Data Sheet: D15

Configurator Number: D10-15A

Date: 03/15/2019

Supersedes: 03/08/2019

Fixed Speed – 60 Hz

PRODUCT DATA		Units	D15
Performance (1)			
Working Pressure	PACKAGE PRESSURE (configurator pick)	psig bar g	145 10
	Airend Model at configurator pressure / Pulley Ratio		DSC-002703 / 1.9
100 psig 6.9 bar g	Capacity (2)	acfm (m ³ /min)	53.5 (1.51)
	Package Input Power - AC (3,4)	kW	12.0
	Specific Power - AC	kW/100 cfm	22.4
	Main Drive Motor Power	bhp	14.5
110 psig 7.6 bar g	Capacity (2)	acfm (m ³ /min)	52.6 (1.49)
	Package Input Power - AC (3,4)	kW	12.5
	Specific Power - AC	kW/100 cfm	23.7
	Main Drive Motor Power	bhp	15.1
125 psig 8.6 bar g	Capacity (2)	acfm (m ³ /min)	51.7 (1.46)
	Package Input Power - AC (3,4)	kW	13.2
	Specific Power - AC	kW/100 cfm	25.6
	Main Drive Motor Power	bhp	16.0
145 psig 10.0 bar g	Capacity (2)	acfm (m ³ /min)	50.3 (1.42)
	Package Input Power - AC (3,4)	kW	14.2
	Specific Power - AC	kW/100 cfm	28.3
	Main Drive Motor Power	bhp	17.2
Unloaded Package Input Power - AC		kW	5.8
Minimum Operating Pressure		psig (bar g)	100 (6.9)
Airend Data			
Drive Type		n/a	Belt
Airend Speed (male rotor)		rpm	6610
Male / Female Rotor Diameter		mm	70.6 / 58.9
Male / Female Rotor Tip Speed		m/s	24.4 / 16.3
General Package Data			
System Capacity - oil		gal (l)	1.0 (3.8)
Oil flow @ configured pressure		gpm (l/min)	4.8 (18)
Air/Oil Reservoir Capacity - oil		gal (l)	0.6 (2.2)
Air/Oil Reservoir Volume - air		ft ³ (l)	0.2 (5.2)
Oil Cooler Heat Rejection		btu/min	525
Aftercooler Heat Rejection		btu/min	100
Radiated Heat Rejection		btu/min	113
Nominal Temperature Rise @ Configured Pressure		°F (°C)	32.4 (18)
Min / Max Operating Temperature		°F (°C)	50 / 104 (10 / 40)
Noise Level Data (5)			
Quiet Enclosed - AC		dB(A)	69

NOTES:

- (1) Capacity and Power measured in accordance with ISO 1217 Annex C.
- (2) acfm is actual cubic feet per minute at inlet conditions
- (3) Package Input Power includes main motor and control input power

- (4) Power noted with ODP motor
- (5) Sound level measurement in accordance with ISO 2151.



Compressed Air Advisors, Inc.

Phone: 877.247.2381

info@compressedairadvisors.com

www.compressedairadvisors.com



D15 ENGINEERING DATA SHEET

Engineering Data Sheet: D15

Configurator Number: D10-15A

Date: 03/15/2019

Supersedes: 03/08/2019

Fixed Speed – 60 Hz

PRODUCT DATA	Units	D15	
Main Drive Motor Data			
Drive Motor Nominal Power	hp (kW)	15 (11.2)	
Drive Motor Speed	rpm	3500	
Drive Motor Service Factor	n/a	1.25	
Drive Motor Minimum Nameplate Efficiency - TEAO	%	91	
Drive Motor Min. Insulation Class	n/a	F	
Drive Motor Nominal Current (Per NEC Code) - 200V 3PH (6)	Amps	48.3	
Drive Motor Nominal Current (Per NEC Code) - 230V 3PH (6)	Amps	42	
Drive Motor Nominal Current (Per NEC Code) - 460V 3PH (6)	Amps	21	
Air Cooled Package Data			
Cooling Fan Motor Speed (7)	rpm	3500	
Fan Motor Nameplate Efficiency	%	N/A	
Total Ventilation Flow Rate	cfm (m ³ /min)	2030 (57.5)	
Max Total Added Static Pressure	in H ₂ O (Pa)	0.1 (25)	
Aftercooler Design Approach Temperature - above amb	°F (°C)	27 (15)	
Connections			
Package type	Units	Base Mounted	120 Gallon with Dryer
Discharge Connection Size	" npt	3/4 (Male)	3/4 (Female)
Moisture Drain Tube Size - Dryer, Filter	mm OD	N/A	6 , 6
Ref. Dryer Power Supply - 1PH	V	N/A	115V/60Hz
Oil Drain Tube Size	" OD	1/2	
Dimensions and Weights			
Package type	Units	Base Mounted	120 Gallon with Dryer
Length	in (mm)	41 (1041)	77 (1956)
Width	in (mm)	27 (686)	27 (686)
Height	in (mm)	37 (940)	63 (1600)
Weight (8)	lbs (kg)	600 (272)	1175 (533)
Outline Drawing - standard package	n/a	D1015-SE	D1015TD-SE

NOTES:

(6) Main motor current per NEC table 430.250 to be used for wire sizing

(7) Cooling fan is mounted on main motor

(8) Weights based on DSC-002703 air end and 15hp/ODP Baldor motor



Compressed Air Advisors, Inc.

Phone: 877.247.2381

info@compressedairadvisors.com

www.compressedairadvisors.com