

SEPREMIUM 130

Oil/water separator for compressor capacities up to 130 CFM

PRODUCT FEATURES

The SEPREMIUM range of oil/water separators separates oil from condensate, generated by compressed air systems. The SEPREMIUM achieves efficient separation of oil from condensate by means of directing the condensate through various filtration stages.

As condensate flows in to the SEPREMIUM, the oil is filtered out through various filtration elements.

The oil adsorbing elements combine various types of adsorption technologies to achieve less than 10 ppm oil residue values at the output stage.

The SEPREMIUM 130 is designed to be versatile and compact.

The elements are lightweight and servicing is a quick and above all clean process.



COMMERCIAL BENEFITS

- Separation of all types of compressor lubricants
- Compact design and small footprint, offering:
 - easy handling
 - flexible installation benefits
- Clothing kit included
- Competitive pricing levels
- Consult JORC for private labelling options


TECHNICAL ADVANTAGES

- High performance filtration materials applied
- Simple, fast and clean installation and maintenance procedure
- Successful separation of mineral oil, synthetic lubricants and stable emulsions
- Test bottle included for routine output testing schedules
- Fixing bracket for wall mounting optionally available
- Brass threaded inlet/outlet, ensuring a secure installation (hose barbs are included)

SEPREMIUM 130

Oil/water separator for compressor capacities up to 130 CFM

DIMENSIONS



Replacement service pack



Routine testing feature incl.

TECHNICAL SPECIFICATIONS

Max. compressor capacity	130 CFM
Max. oil adsorption in the elements	1 gallon
Brass inlet connection	1/2" (hose barb included)
Brass outlet connection	1/2" (hose barb included)
TEST kit	Yes
Target output value	<10 ppm
Housing material	PE
Total recyclable	Yes
Housing colour	Black
Lid colour	Grey
Ambient and Media temperature*	34 - 131 °F

*Avoid placing oil/water separators in direct sunlight as this might expose the unit to temperatures that could exceed maximum temperature specifications.



Fixing bracket available

SEPARATION OF:

Mineral lubricants	Yes
Synthetic lubricants	Yes
Stabile condensate emulsions*	Yes
Ultra-Coolant*, Sigma Mol*	Yes
Roto-Inject*	Yes

*Ultra-Coolant, Sigma Mol and Roto-Inject are registered trade names of producers of compressor lubricants.

The SEPREAMIUM 130 can be applied as a stand-alone item or as part of an integrated package of the compressor system. The compact size allows for easy installation inside compressor packages.

JORC is NEN - EN - ISO 9001:2015 certified

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition, JORC reserves the right to revise information without notice and without incurring any obligation.