

CAA-2015-XX

2015 utilizes the latest high-performance, full-synthetic base stocks and additives. This formulation offers an exceptional level of protection against wear, rust and corrosion, as well as outstanding resistance against oxidation and thermal breakdown.

2015 is designed to provide 8,000+ hours of service.

ATTRIBUTES

- 8,000-hour oil life at 100°C discharge temperature
- Excellent thermal stability
- Resists water contamination
- Saves energy
- High flash point
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

2015 Grades	32	46	68	100
Viscosity cSt @ 40°C	30.4	45	64	105
Viscosity cSt @ 100°C	5.3	6.5	8.57	12.33
Flash Point °F (°C)	430 (221)	445 (229)	451 (233)	503 (262)
Demulsibility, 130°F, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0