

# FSC-MAX FLUID ST



## FSC-1000

### PREMIUM RECIPROCATING FLUID

FSC-1000 partial-synthetic blend air compressor lubricant is designed for reciprocating compressors. Utilizing an advanced-technology additive system, FSC-1000 offers good oxidative and thermal stability as well as resistance to carbon and varnish formation. FSC-1000 gives outstanding service — even in moderately severe operating conditions.

#### ATTRIBUTES

- Good oxidative and thermal stability
- High viscosity index
- Controls carbon and varnish formation
- High flash and auto-ignition points
- Non-toxic/non-hazardous

#### TYPICAL LUBRICANT PROPERTIES

##### **FSC-1000 Viscosities** **68**

Viscosity cSt @ 40°C	68
Viscosity cSt @ 100°C	8.8
Viscosity Index	102
Flash Point °F (°C)	431 (222)
Pour Point °F (°C)	-23 (-31)
Copper Corrosion, 24 Hr	1a
Demulsibility, 130°F, 30 Min	40/40/0

**COMPRESSED**  
AIR ADVISORS  
Inc.

**Compressed Air Advisors, Inc.**

Phone: 877.247.2381

[info@compressedairadvisors.com](mailto:info@compressedairadvisors.com)

[www.compressedairadvisors.com](http://www.compressedairadvisors.com)