

CAROMA

Revision: 0

Date: 18/04/2024


Supersedes all previous issues

Contura II Cleanflush™ Invisi II

4.5/3 litre Dual Flush Toilet Suite with
Contura II Cleanflush™ Wall Faced Rimless Vitreous
China Pan and Invisi II Cistern for Inwall, Under
Counter, Induct or Inceiling applications



cleanflush



CAROMA

4.5/3 litre Dual Flush Toilet Suite with Contura II Cleanflush™ Vitreous China Wall Faced Rimless Pan and Invisi II Cistern for Inwall, Under Counter, Induct or Inceiling applications

Contura II Cleanflush™ Invisi II



Toilet Suite pictured in White (W) colour option.

Embrace natural luxury with the Caroma Contura Collection - sculptural design with an organic simplicity to create a sense of subtle indulgence for your bathroom. The suite comprises of the **Contura II Cleanflush™** pan and trusted Caroma **Invisi II** cistern to offer a seamless finish to any domestic or commercial bathroom.

Combining industry leading rimless pan technology and GermGard® Antibacterial Protection; a unique technology which kills harmful bacteria, **Cleanflush™** is a superior flushing system suitable for domestic and commercial applications. Incorporating several patented technologies: Caroma Flow Splitter™, Caroma Flow Balancer™ and Caroma Uni-Orbital® Connector, the Cleanflush™ pan is innovative and the next evolution in toilets. The Flow Splitter evenly flows water around the top of the bowl to meet at the Flow Balancer which directs the water powerfully into the sump, reducing the need for brush cleaning. The rimless pan is easy to clean and unlike traditional pan profiles, provides full visibility of any grime build up. Caroma Cleanflush™ provides a cleaner clean for peace of mind.

The adjustable flush pipe is a new feature for the Invisi II system. If the pan inlet hole is higher than the flush pipe due to floor tiling height variations, the flush pipe can be raised by up to 25mm.

The pan connection system includes the patented Caroma Uni-Orbital® Connector for increased installation flexibility. The Caroma Uni-Orbital® Connector extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm – 120mm with a recommended setout of 90mm.

Pan: **Contura II Cleanflush™** wall faced back inlet 4.5 litre full flush rimless pan.

Traps: Universal trap for S or P-trap installations.

Inlet: Fully glazed 50mm back inlet for concealed cistern.

Cisterns and Flushvalves: **Invisi II Cistern** – suitable for inwall, under counter, induct and in ceiling applications. The Contura II Round Push Buttons and Access Plate (supplied separately) are available in 5 finishes: Chrome (C), Black (B), Brushed Brass (BB), Brushed Bronze (BBZ) and Brushed Nickel (BN). Code No.848810.

Fixing: The pan can be fixed to the floor by either bedding into mortar or using the supplied D82 Concealed Fixing Bracket.

Seats: The **Contura II** soft close quick release thermoset toilet seat with GermGard® Antibacterial Protection is provided as standard with seat caps in Stainless Steel. Optional seat caps are available in Brushed Bronze (BBZ). Seat available in three (3) colour options: White (W), Matte White (MW) and Clay (CL). Code No.300085.

Colours: White (W), Matte White (MW) and Clay (CL).

Installation: The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Other Available Colour Options:



Adjustable flush pipe included

Contura II Cleanflush™ Invisi II
4.5/3 litre Wall Faced Toilet Suite
with Back Inlet Pan, Internal Overflow
Cistern and Seat with Stainless Steel
Seat Caps:

Code No.	Colour Options:
848901	W, MW, CL

Button options: see 6.15.1

All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Inwall Installation

90 recommended setout, range 60 – 120 (up to 50mm sideways adjustment)

Under Counter Installation
(optional under counter flush pipe 237222 is required)

Note: access to cistern internals can be achieved through either front or top mount button plate option.