

Bolton600 Black Ultra Low-Loss Cable Spool

Priced Per Meter, Equivalent to LMR600®



BT51458

Bolton600 by the foot ultra low-loss coax cable for commercial & industrial installations.

- Ultra Low Loss 50ohm Cable
- Meets LMR®600 Specifications
- Connectors and termination sold separately
- Priced per Meter



CABLE STUFF

Product Specifications may change without prior notice.

Shielding - AL/P-Foil(Bonded)	Foil overlap	≥ 115 %
Outer Conductor - TC Wire Braid	Conductor Diameter	0.0070 in +/- .0003 in, 0.180 mm +/- 0.008 mm
	Number of Wires	240
Jacket - Oil + PE	Coverage	90 +/-3%
	Outer Diameter	0.5901 in +/- .001 in, 14.99 mm +/-0.15 mm
	Color	Black

MECHANICAL STUFF

Minimum Bending Radius:	Installation	1.52 in, 38.5 mm
	Repeated	6.02 in, 153 mm
Max Pulling Tension		1750 N
Crush resistance of cable (load of 700N)		< 1 %
Rated Temperature	Storage/operating Temperature	-40°F to 185°C, -40° to 85°C

ELECTRICAL STUFF

Attenuation (68°F, 20°C)	dB/100ft	dB/100m
30 MHz	0.40	1.40
50 MHz	0.50	1.80
150 MHz	1.00	3.20
220 MHz	1.20	3.90
450 MHz	1.70	5.60
900 MHz	2.50	8.20
1500 MHz	3.30	10.90
1800 MHz	3.70	12.10
2000 MHz	3.90	12.80
2500 MHz	4.40	14.50
5800 MHz	7.30	23.80



QUESTIONS? CALL US TODAY
+27 011 749 3085



sales@boltontechnical.co.za



www.boltontechnical.co.za

