Ultra High Gain Outdoor Antenna



BT684250

Empower Your Reach: Unlock Unmatched Signal Strength and Extended Distances with Our High-Gain Outdoor Panel Antenna

- Spans 698MHz to 2700MHz for broad connectivity.
- High Gain: Ranges from 9.5dBi to 15.5dBi, ensuring robust signal strength.
- Vertical Polarization: Optimized for improved reception quality.
- Extended Outdoor Reach: Provides large distance coverage for outdoor applications.




ELECTRICAL STUFF

		Troduce	opeenieutions may	enange menoar pr		RADIATION
Item No.	BT684250					PATTERNS
Frequency Range	MHz	698-824	825-960	1710-2170	2171-2700	HORIZONTAL
Max Gain	dBi	10.5	12	15	15.5	
VSWR		≤1.7:1	≤1.7:1	≤1.7:1	≤1.7:1	18 ± 25
Polarization	Horizontal					
	Vertical					698-960MHz
PIM, 3rd Order, 2 x 2 W						
Input Power, maximum	watt					
Impedance	ohm		1 and			

Product Specifications may change without prior

MECHANICAL STUFF

			1
Connector Type		N-Female	VERTICAL
Size	mm	660x287x132	T LINTER L
Antenna Weight	kg	5.5	(D)
Operational Temperature	oC, oF	-40 to +60	
Radome Material and Color		UPVC, RAL7035	
Operational Humidity	%	<95	698 -960MHz





1710 -2700MHz

1710-2700MHz

QUESTIONS? CALL US TODAY 011 749 3085 ☑ sales@boltontechnical.co.za
⊕ www.boltontechnical.co.za

JT Business Park, Unit 4
5 Rydal Lane, Longlake, 1609