

SPECIFICATIONS

MBA Hard Surface RIGID CORE Collection with Acoustic Pad	
Overall Thickness	6.5 MM (5MM RIGID CORE WITH 1.5MM IXPE PAD)
Plank Size	7"X48"X6.5MM
Wear Layer	.50MM (20MIL) WITH CERAMIC FINISH
Printed Design	WOOD VISUAL EMBOSSING
Surface Finish	UV CURED COATING WITH 7% GLOSS
Edge Profile	4 SIDED MICRO BEVEL
Installation	VALINGE 2G EASY DROP LOCKING SYSTEM FLOATING
Impact Isolation class	IIC 73
Sound Transmission Class	STC 71
Phthalate Free	E1
Slip Resistance	DS
Fire Behavior	B FL S1
Indoor Air Quality	FLOOR SCORE
Recyclable	100%
Dimensional Stability	ASTM F2199-09(2014)PASS
Resistance to Chemicals	ASTM F925-13 PASS
Abrasion Resistance	ASTM D4060-14 SCRATCH RESISTANCE
In floor heating	IN SLAB, RADIANT HEAT ONLY MAX (28 DEGREE CELICIUS)
Limited warranty	LIFETIME RESIDENTIAL AND 10 YEAR LIMITED COMMERCIAL
Packaging: Plank/box	8
Coverage:Sq.Ft/Box	18.91
Weight	37 LBS
ALL Mouldings-94"	EXACT MATCH, FLUSH NOSING, REDUCER, T-MOULDING





















