




SPECIFICATIONS

MBA Hard Surface RIGID CORE 5G with Acoustic Pad

Overall Thickness	6.5MM (5.5MM RIGID CORE WITH 1MM IXPE PAD)
Plank Size	Classic: 7"X48"X6.5 mm Chevron: 4.72" x 27.16" x 6.5 mm
Wear Layer	0.5mm (20 MIL) with ceramic finish
Printed Design	Wood Visual - New Silver Chain Embossing Pattern
Surface Finish	UV Cured Coating with 7% Gloss
Edge Profile	6 COLORS MICROBEVEL
Installation	VALINGE 5G FLOATING LOCKING SYSTEM ALLOWS STRONGER CONNECTING END JOINTS
Impact Isolation class	IIC 73
Sound Transmission Class	STC 71
Phthalate Free	E1
Slip Resistance	DS
Fire Behavior	B FL S1
Indoor Air Quality	FLOOR SCORE
Recyclable	100%
Dimensional Stability	ASTM F2199-09(2014)PASS
Resistance to Chemicals	ASTM F925-13 PASS
Abrasion Resistance	ASTM D4060-14 SCRATCH RESISTANCE
In floor heating	IN SLAB, RADIANT HEAT ONLY (MAX 28°C)
Limited warranty	LIFETIME RESIDENTIAL AND 10 YEAR LIMITED COMMERCIAL
Packaging: Plank/box	10
Coverage: Sq.Ft/Box	Classic: 18.91 Chevron: 12.48
Weight	Classic: 38.6 lbs Chevron: 28.4 lbs
ALL Mouldings-94"	EXACT MATCH, FLUSH NOSING, REDUCER, T-MOULDING



Installation type:
Valinge 5G Locking
System Floating



CERTIFIED BY
SCS Global Services

